



**Product Features**

- Solid-state linear design
- Small and light weight
- Suitable for US-PCS
- 50 Ohm Input/Output impedance
- High reliability and ruggedness
- Built in Output Isolator
- Built in monitoring circuit
- High efficiency

**Application**

- LTE RRH



**Description**

This HPA Module is a high gain, wide dynamic range amplifier module.  
 Custom design available.

**Electrical Specification @ VDD= 45V, 50Ω System**

Parameter	Symbol	Specification @ 25 °C		
Frequency Range	BW	1805MHz ~ 1880MHz		
Operating Bandwidth within BW	OBW	5~75MHz		
Average Output Power	Pout	49dBm(80W) Avg. @ LTE 1FA 10MHz		
Peak Output Power	Psat	56.5dBm (Min.)@ Duty 10% Pulse		
ACLR (LTE 1FA 10MHZ) @ Po=+49dBm (max.)	ACLR	Non-DPD	-26dBc(Min) @±10MHz	@-30 ~ +65°C
		With-DPD	-53dBc(Min) @±10MHz	@ 45V @ CFR 7.5dB
RF Gain @ 25°C	G	57.0dB (Min.)		
Gain Flatness	ΔG	within 3.0dB over Operating Frequency Range		
Gain Variation with Temperature	G	±3dB		
Input Return Loss	S11	-12dB (Max.)		
Output Return Loss	S22	-17dB (Max.)		
Operating Voltage	VDC	V <sub>DD</sub> (Main/Drive Amp) : +45Vdc , +5.6Vdc		
Current Consumption	IDD	IDD : +45Vdc : 4.4A (Typ.) & +5.6Vdc : 360mA(Tpy.)		
Efficiency	Eff	40%(Typ.)		
Feedback Output level @ 49dBm	FB	10dBm ± 1.5dBm		
Temp Detector	T	0.90V @ 40 °C		

**Environmental Characteristics**

Parameter	Symbol	Min.	Typ.	Max.	Unit
Operating Ambient Temperature	Ta	-30		+65	°C
Storage Temperature	Tstg	-40		+130	°C
Relative humidity w/o condensation	RH			95	%

**Maximum Ratings**

Input Overdrive	P <sub>OD</sub>	-2dBm		Max.
Load VSWR	Ψ	∞ : 1 (All Phase & Amplitude)		Nom.
Operating Case Temperature	Tc	+90		°C

**Interface Connector**

**8-Pin-Control (MOLEX\_5267\_08)**

Pin #	Description	Specifications
1	Vcc	+5.6V
2	Vcc	+45V
3	Vcc	+45V
4	Vcc	+45V
5	GND	GROUND
6	GND	GROUND
7	GND	GROUND
8	GND	GROUND


**4Pin-Control (SMW200-04P)**

Pin #	Description	Specifications
1	Enable/Disable	Amp Enable(+5.6V) / Amp Disable(+0V)
2	GND	GROUND
3	GND	GROUND
4	Temp DET	Temp Sense (900mV @ 40°C)

**Mechanical Specifications**


Parameter	Value	Units	Limits
Dimensions	162(W) × 125(L) × 18.8(H)	mm	
Weight	0.75(max)	Kg	
RF Input Connector	SMA(Female)		
RF Output Coupling Connector	SMA(Female)		
RF Output Connector	SMA(Female)		
I/O Connector	SMW200 4pin(Male)		
	Molex 8pin(Male)		
Cooling	External Heat-sink		

**Outline Drawing**



\*Note : Connector positions and module mount holes may be subjected change.

Block Diagram



**Test Data** (Test Results: DPD Operation)

**Test Equipments**


- DPD Engine : Optichron OP6180 Board
- Signal Generator : E4438C (Agilent)
- Spectrum Analyzer : E4440A (Agilent)
- Network Analyzer : 8753ES (Agilent)
- Power Supply : 6674A (Agilent)

**Test Condition**

- Signal : LTE 1FA 10MHz(PAPR 7.5dB)
- CFR apply
- AMP Temperature: 40°C

**Network Analyzer Data**

**• Gain (S21)**



**• Input VSWR (S11)**




**• Output VSWR (S22)**




**Spectrum Analyzer Data**


• Pre – DPD @ 1810MHz




• Post- DPD @ 1810MHz




• Pre – DPD @ 1842.5MHz




• Post- DPD @ 1842.5MHz




**Pre – DPD @ 1875MHz**



**Post- DPD @ 1875MHz**



**Pulse Duty 10% @ 1842.5MHz**



RFHIC Corporation (RFHIC) reserves the right to make changes to any products herein or to discontinue any product at any time without notice. RFHIC do not assume any liability for the suitability of its products for any particular purpose, and disclaims any and all liability, including without limitation consequential or incidental damages. The product specifications herein expressed have been carefully checked and are assumed to be reliable. However, RFHIC disclaims liability for inaccuracies and strongly recommends buyers to verify that the information they are using is current before placing purchase orders. RFHIC products are not intended for use in life support equipment or application where malfunction of the product can be expected to result in personal injury or death. Buyer uses or sells such products for any such unintended or unauthorized application, buyer shall indemnify, protect and hold RFHIC and its directors, officers, stockholders, employees, representatives and distributors harmless against any and all claims arising out of such use. RFHIC's liability under or arising out of damages, claims of whatsoever kind and nature which RFHIC products could cause shall be limited in amount to the net purchase price of the products sold to buyer by RFHIC.