

## This document was generated on 05/08/2012 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

| 10-18-1031   |   |  |
|--------------|---|--|
|              |   | $\land$  |
|              |   |  |
|              | redevel 002" Discord Contract Llonder, Chrouded 2 Circuite 2 Male |  |
|              | Indard .093" Pin and Socket Header, Shrouded, 3 Circuits, 2 Male  |  |
| Terminais    |   |  |
|              |   |  |
|              | Del 19 Certificate of Compliance (DDE)                            |  |
|              | ROHS Centificate of Compliance (PDF)                              |  |
|              |   | Serie  |
| tion         |   | image - Reference only   |
|              | L P10080  |  |
|              |   | EU RoHS China RoHS   |
|              | E29179  | ELV and RoHS   |
|              |   | Compliant  |
|              | PCB Headers   | REACH SVHC   |
|              |   | Contains SVHC: No  |
|              |   | Low-Halogen Status   |
|              | ,   | Not Low-Halogen  |
|              |   |  |
|              | Standard .093"  | Need more information on product   |
|              |   | environmental compliance?  |
|              |   | Email productcompliance@molex.com  |
|              |   | For a multiple part number RoHS Certificate  |
|              |   | Compliance, <u>click here</u>  |
|              |   |  |
|              |   | Please visit the <u>Contact Us</u> section for any   |
| les max)     |   | non-product compliance questions.  |
|              |   | I  |
|              |   |  |
|              |   |  |
|              |   | Search Parts in this Series  |
| nination     |   | <u>3099</u> Series   |
|              |   |  |
|              | -   | Mates With   |
|              |   | <u>03091081</u> , <u>03091032</u>  |
|              |   | ,  |
|              |   |  |
| ommonded     |   |  |
|              |   |  |
| 2            |   |  |
|              |   |  |
|              |   |  |
|              |   |  |
| atible (SMC) |   |  |
|              |   |  |
|              | Through Hole  |  |
| -            | -   |  |
| 0            | 54  |  |
| er Contact   |   |  |
|              | 250V  |  |
|              |   |  |
|              | 3099P3  |  |
|              | Active<br>Standard .093"  | Standard .093"   2.36mm Diameter Standard .093" Pin and Socket Header, Shrouded, 3 Circuits, 2 Male Terminals   ReHS Certificate of Compliance (PDF)   tion   LR19980<br>E29179   PCB Headers<br>3099   Power, Wire-to-Board<br>Solder Type Round Pin<br>Standard .093"   No   a standard .093"   No   Yes   ing Tin   mination Tin   Vetical 4.32mm   Yes Non   Yes None   ommended 1.60mm   Bag Su3mm   Yes Fully   No Yes   Fully No   Yes Fully   No Yes   stable (SMC) No   Operating -40°C to +105°C   Style Through Hole   er Contact 5A   250V Sol |

This document was generated on 05/08/2012 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION