

## General Description

The AOB414 uses advanced trench technology to provide excellent  $R_{DS(ON)}$ , shoot-through immunity and body diode characteristics. This device is ideally suited for use as a low side switch in CPU core power conversion. AOB414L (Green Product) is offered in a lead-free package.

## Features

$V_{DS}$  (V) = 30V

$I_D$  = 110A

$R_{DS(ON)} < 4.2\text{m}\Omega$  ( $V_{GS} = 10\text{V}$ )

$R_{DS(ON)} < 4.8\text{m}\Omega$  ( $V_{GS} = 4.5\text{V}$ )



### Absolute Maximum Ratings $T_A=25^\circ\text{C}$ unless otherwise noted

Parameter	Symbol	Maximum	Units
Drain-Source Voltage	$V_{DS}$	30	V
Gate-Source Voltage	$V_{GS}$	$\pm 12$	V
Continuous Drain Current <sup>B,G</sup>	$I_D$	110	A
$T_C=100^\circ\text{C}$ <sup>B</sup>		80	
Pulsed Drain Current	$I_{DM}$	200	
Avalanche Current <sup>C</sup>	$I_{AR}$	30	A
Repetitive avalanche energy $L=0.1\text{mH}$ <sup>C</sup>	$E_{AR}$	140	mJ
Power Dissipation <sup>B</sup>	$P_D$	100	W
$T_C=100^\circ\text{C}$		50	
Power Dissipation <sup>A</sup>	$P_{DSM}$	3.1	W
$T_A=70^\circ\text{C}$		2	
Junction and Storage Temperature Range	$T_J, T_{STG}$	-55 to 175	°C

### Thermal Characteristics

Parameter	Symbol	Typ	Max	Units
Maximum Junction-to-Ambient <sup>A</sup>	$R_{\theta JA}$	8.1	12	°C/W
Maximum Junction-to-Ambient <sup>A</sup>		33	40	°C/W
Maximum Junction-to-Lead <sup>C</sup>	$R_{\theta JL}$	0.84	1.5	°C/W

**Electrical Characteristics ( $T_J=25^\circ\text{C}$  unless otherwise noted)**

Symbol	Parameter	Conditions	Min	Typ	Max	Units
<b>STATIC PARAMETERS</b>						
$\text{BV}_{\text{DSS}}$	Drain-Source Breakdown Voltage	$I_D=250\mu\text{A}, V_{GS}=0\text{V}$	30			V
$I_{\text{DSS}}$	Zero Gate Voltage Drain Current	$V_{DS}=24\text{V}, V_{GS}=0\text{V}$ $T_J=55^\circ\text{C}$		1		$\mu\text{A}$
				5		
$I_{\text{GSS}}$	Gate-Body leakage current	$V_{DS}=0\text{V}, V_{GS} = \pm 12\text{V}$			100	nA
$V_{\text{GS(th)}}$	Gate Threshold Voltage	$V_{DS}=V_{GS}, I_D=250\mu\text{A}$	0.8	1.1	1.5	V
$I_{\text{D(ON)}}$	On state drain current	$V_{GS}=4.5\text{V}, V_{DS}=5\text{V}$	110			A
$R_{\text{DS(ON)}}$	Static Drain-Source On-Resistance	$V_{GS}=10\text{V}, I_D=30\text{A}$ $T_J=125^\circ\text{C}$		3.2	4.2	$\text{m}\Omega$
			5	6		
		$V_{GS}=4.5\text{V}, I_D=30\text{A}$		3.8	4.8	$\text{m}\Omega$
$g_{\text{FS}}$	Forward Transconductance	$V_{DS}=5\text{V}, I_D=30\text{A}$		102		S
$V_{\text{SD}}$	Diode Forward Voltage	$I_S=1\text{A}, V_{GS}=0\text{V}$		0.64	1	V
$I_S$	Maximum Body-Diode Continuous Current				110	A
<b>DYNAMIC PARAMETERS</b>						
$C_{\text{iss}}$	Input Capacitance	$V_{GS}=0\text{V}, V_{DS}=15\text{V}, f=1\text{MHz}$		9130		pF
$C_{\text{oss}}$	Output Capacitance			625		pF
$C_{\text{rss}}$	Reverse Transfer Capacitance			387		pF
$R_g$	Gate resistance	$V_{GS}=0\text{V}, V_{DS}=0\text{V}, f=1\text{MHz}$		0.4		$\Omega$
<b>SWITCHING PARAMETERS</b>						
$Q_g(4.5\text{V})$	Total Gate Charge	$V_{GS}=4.5\text{V}, V_{DS}=15\text{V}, I_D=30\text{A}$		72.4		nC
$Q_{\text{gs}}$	Gate Source Charge			12.8		nC
$Q_{\text{gd}}$	Gate Drain Charge			18.4		nC
$t_{\text{D(on)}}$	Turn-On Delay Time	$V_{GS}=10\text{V}, V_{DS}=15\text{V}, R_L=0.5\Omega, R_{\text{GEN}}=3\Omega$		15		ns
$t_r$	Turn-On Rise Time			29.2		ns
$t_{\text{D(off)}}$	Turn-Off Delay Time			106.5		ns
$t_f$	Turn-Off Fall Time			52		ns
$t_{\text{rr}}$	Body Diode Reverse Recovery Time	$I_F=30\text{A}, dI/dt=100\text{A}/\mu\text{s}$		31.2		ns
$Q_{\text{rr}}$	Body Diode Reverse Recovery Charge	$I_F=30\text{A}, dI/dt=100\text{A}/\mu\text{s}$		20.3		nC

A: The value of  $R_{\text{JJA}}$  is measured with the device mounted on 1in<sup>2</sup> FR-4 board with 2oz. Copper, in a still air environment with  $T_A=25^\circ\text{C}$ . The Power dissipation  $P_{\text{DSM}}$  is based on steady-state  $R_{\text{JJA}}$  and the maximum allowed junction temperature of 150°C. The value in any given application depends on the user's specific board design, and the maximum temperature of 175°C may be used if the PCB or heatsink allows it.

B. The power dissipation  $P_D$  is based on  $T_{J(\text{MAX})}=175^\circ\text{C}$ , using junction-to-case thermal resistance, and is more useful in setting the upper dissipation limit for cases where additional heatsinking is used. It is used to determine the current rating, when this rating falls below the package limit.

C: Repetitive rating, pulse width limited by junction temperature  $T_{J(\text{MAX})}=175^\circ\text{C}$ .

D. The  $R_{\text{JJA}}$  is the sum of the thermal impedance from junction to case  $R_{\text{JJC}}$  and case to ambient.







E. The static characteristics in Figures 1 to 6 are obtained using <300μs pulses, duty cycle 0.5% max.

F. These tests are performed with the device mounted on 1 in<sup>2</sup> FR-4 board with 2oz. Copper, in a still air environment with  $T_A=25^\circ\text{C}$ . The SOA curve provides a single pulse rating.

G. The maximum current rating is limited by the package current capability.

THIS PRODUCT HAS BEEN DESIGNED AND QUALIFIED FOR THE CONSUMER MARKET. APPLICATIONS OR USES AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS ARE NOT AUTHORIZED. AOS DOES NOT ASSUME ANY LIABILITY ARISING OUT OF SUCH APPLICATIONS OR USES OF ITS PRODUCTS. AOS RESERVES THE RIGHT TO IMPROVE PRODUCT DESIGN, FUNCTIONS AND RELIABILITY WITHOUT NOTICE.

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS



### TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Figure 7: Gate-Charge Characteristics




Figure 8: Capacitance Characteristics




Figure 9: Maximum Forward Biased Safe Operating Area (Note F)




Figure 10: Single Pulse Power Rating Junction-to-Ambient (Note F)




Figure 11: Normalized Maximum Transient Thermal Impedance (Note F)

---

### TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Figure 12: Single Pulse Avalanche capability




Figure 13: Power De-rating (Note B)




Figure 14: Current De-rating (Note B)