



MB220F

SURFACE MOUNT SCHOTTKY BARRIER RECTIFIER

VOLTAGE 200 Volts **CURRENT** 2 Amperes

SMBF



Unit : inch(mm)

FEATURES

- Plastic package has Underwriters Laboratory Flammability Classification 94V-O
- For surface mounted applications
- Low profile package
- Built-in strain relief
- Metal to silicon rectifier, majority carrier conduction
- Low power loss, high efficiency
- High surge capacity
- For use in low voltage high frequency inverters, free wheeling, and polarity protection applications
- Lead free in comply with EU RoHS 2002/95/EC directives.
- Green molding compound as per IEC61249 Std. . (Halogen Free)

MECHANICAL DATA

- Case: SMBF molded plastic
- Terminals: Solder plated, solderable per MIL-STD-750, Method 2026
- Approx. Weight: 0.0018 ounces, 0.05 grams
- Polarity : Color band denotes cathode end



MAXIMUM RATINGS (TA=25°C unless otherwise noted)

PARAMETER	SYMBOL	J5 @ 9	UNITS
Recurrent Peak Reverse Voltage	V _{RRM}	200	V
RMS Voltage	V _{RMS}	140	V
DC Blocking Voltage	V _R	200	V
Average Forward Current	I _{F(AV)}	2	A
Peak Forward Surge Current : 8.3ms single half sine-wave superimposed on rated load(JEDEC method)	I _{FSM}	50	A
Typical Thermal Resistance ,Junction to Lead (Note 1) Junction to Ambient (Note 1)	R _{θJL} R _{θJA}	20 62.5	°C / W
Operating Junction Temperature and Storage Temperature Range	T _J , T _{STG}	-55 to +150	°C

NOTES :

1. Mounted on 48cm² FR-4 PCB.



MB220F

ELECTRICAL CHARACTERISTICS ($T_A=25^\circ\text{C}$ unless otherwise noted)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN.	TYP.	MAX.	UNIT
Breakdown voltage	V_{BR}	$I_R=1\text{mA}$ $T_A=25^\circ\text{C}$	200	-	-	V
Instantaneous forward voltage	V_F	$I_F=0.1\text{A}$ $T_A=25^\circ\text{C}$	-	0.57	-	V
		$I_F=1\text{A}$ $T_A=25^\circ\text{C}$	-	0.77	-	V
		$I_F=2\text{A}$ $T_A=25^\circ\text{C}$	-	0.83	0.9	V
	V_F	$I_F=0.1\text{A}$ $T_A=125^\circ\text{C}$	-	0.43	-	V
		$I_F=1\text{A}$ $T_A=125^\circ\text{C}$	-	0.61	-	V
		$I_F=2\text{A}$ $T_A=125^\circ\text{C}$	-	0.68	-	V
Reverse current	I_R	$V_R=160\text{V}$ $T_A=25^\circ\text{C}$	-	0.11	-	μA
		$V_R=200\text{V}$ $T_A=25^\circ\text{C}$ $T_A=125^\circ\text{C}$	-	0.28	50	μA
			-	140.7	-	μA

RATING AND CHARACTERISTIC CURVES




Fig.1 Forward Current Derating Curve




Fig.2 Typical Junction Capacitance




Fig.3 Typical Reverse Characteristics





Fig.4 Typical Forward Characteristics



MB220F

MOUNTING PAD LAYOUT



ORDER INFORMATION

- Packing information
T/R - 5K per 13" plastic Reel

LEGAL STATEMENT

Copyright PanJit International, Inc 2012

The information presented in this document is believed to be accurate and reliable. The specifications and information herein are subject to change without notice. Pan Jit makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose. Pan Jit products are not authorized for use in life support devices or systems. Pan Jit does not convey any license under its patent rights or rights of others.



MB220F

For example :

RB500V-40_R2_00001

Part No.

- Serial number
- Version code means HF
- Packing size code means 13"
- Packing type means T/R

Packing Code XX				Version Code XXXXX		
Packing type	1 st Code	Packing size code	2 nd Code	HF or RoHS	1 st Code	2 nd ~5 th Code
T/B	A	N/A	0	HF	0	serial number
T/R	R	7"	1	RoHS	1	serial number
B/P	B	13"	2			
T/P	T	26mm	X			
TRR	S	52mm	Y			
TRL	L	PBCU	U			
FORMING	F	PBCD	D			

Part No_packing code_Version

MB220F_R1_00001

MB220F_R2_00001

MB220F_00001