



TAYCHIPST

PLASTIC SILICON RECTIFIER

ERA15-01 THRU ERA15-10


50V-1000V 1.0A

FEATURES

- Low cost
- Diffused junction
- Low leakage
- Low forward voltage drop
- High current capability
- Easily cleaned with Freon,Alcohol,Isopropanol and similar solvents
- The plastic material carries U/L recognition 94V-0

MECHANICAL DATA

- Case:JEDEC DO--41,molded plastic
- Terminals: Axial lead ,solderable per MIL- STD-202,Method 208
- Polarity: Color band denotes cathode
- Weight: 0.012ounces,0.34 grams
- Mounting position: Any



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.

Single phase,half wave,60 Hz,resistive or inductive load. For capacitive load,derate by 20%.

		ERA15 -01	ERA15 -02	ERA15 -04	ERA15 -06	ERA15 -08	ERA15 -10	UNITS
Maximum recurrent peak reverse voltage	V_{RRM}	100	200	400	600	800	1000	V
Maximum RMS voltage	V_{RMS}	70	140	280	420	560	700	V
Maximum DC blocking voltage	V_{DC}	100	200	400	600	800	1000	V
Maximum average forward rectified current 9.5mm lead length, @ $T_A=75^\circ C$	$I_{F(AV)}$	1.0						A
Peak forward surge current 8.3ms single half-sine-wave superimposed on rated load @ $T_J=125^\circ C$	I_{FSM}	40.0						A
Maximum instantaneous forward voltage @ 1.0 A	V_F	1.0						V
Maximum reverse current @ $T_A=25^\circ C$ at rated DC blocking voltage @ $T_A=100^\circ C$	I_R	5.0 50.0						μA
Typical junction capacitance (Note1)	C_J	15						pF
Typical thermal resistance (Note2)	$R_{\theta JA}$	50						$^\circ C/W$
Operating junction temperature range	T_J	- 55---- + 150						$^\circ C$
Storage temperature range	T_{STG}	- 55---- + 150						$^\circ C$

NOTE: 1. Measured at 1.0MHz and applied reverse voltage of 4.0V DC.
2. Thermal resistance from junction to ambient.



RATINGS AND CHARACTERISTICS CURVES

ERA15-01 THRU ERA15-10

FIG.1 – TYPICAL FORWARD CHARACTERISTIC




FIG.2 – TYPICAL JUNCTION CAPACITANCE




FIG.3 – PEAK FORWARD SURGE CURRENT




FIG.4 – FORWARD DERATING CURVE




FIG.5 – TYPICAL FORWARD CHARACTERISTIC

