

CentralTM Semiconductor Corp.

145 Adams Avenue, Hauppauge, NY 11788 USA
Tel: (631) 435-1110 • Fax: (631) 435-1824

Manufacturers of World Class Discrete Semiconductors

1N746A THRU 1N759A

500 mW ZENER DIODE
3.3 VOLTS to 12 VOLTS
5% TOLERANCE

JEDEC DO-35 CASE

DESCRIPTION

The Central Semiconductor 1N746A Series Silicon Zener Diode is a high quality voltage regulator for use in industrial, commercial, entertainment and computer applications.

ABSOLUTE MAXIMUM RATINGS

Power Dissipation (@ $T_L = 75^\circ\text{C}$)
Operating and Storage Temperature
Tolerance "A Suffix"
Tolerance "C Suffix"
Tolerance "D Suffix"

SYMBOL

PD 500
T_J, T_{STG} -65 to +200
±5
±2
±1

UNIT

mW
°C
%
%

ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$), $V_F = 1.5\text{V MAX @ } I_F = 200\text{ mA}$ FOR ALL TYPES.

TYPE	Zener Voltage $V_Z @ I_{ZT}$	Test Current I_{ZT}	Maximum Zener Impedance $Z_{ZT} @ I_{ZT}$	Maximum Reverse Leakage Current				Maximum Zener Current I_{ZM}
				$I_R @ V_R$		$I_R @ V_R$ $T_A = 150^\circ\text{C}$		
				μA	Volts	μA	Volts	
1N746A	3.3	20	28	10	1.0	30	1.0	110
1N747A	3.6	20	24	10	1.0	30	1.0	100
1N748A	3.9	20	23	10	1.0	30	1.0	95
1N749A	4.3	20	22	2.0	1.0	30	1.0	85
1N750A	4.7	20	19	2.0	1.0	30	1.0	75
1N751A	5.1	20	17	1.0	1.0	20	1.0	70
1N752A	5.6	20	11	1.0	1.0	20	1.0	65
1N753A	6.2	20	7.0	0.1	1.0	20	1.0	60
1N754A	6.8	20	5.0	0.1	1.0	20	1.0	55
1N755A	7.5	20	6.0	0.1	1.0	20	1.0	50
1N756A	8.2	20	8.0	0.1	1.0	20	1.0	45
1N757A	9.1	20	10	0.1	1.0	20	1.0	40
1N758A	10	20	17	0.1	1.0	20	1.0	35
1N759A	12	20	30	0.1	1.0	20	1.0	30