

ADAM-2510Z

Wireless Router Node

NEW



R&TTE SRRC FCC CE RoHS

Features

- Easy maintenance and field installation
- Low duty wireless communication
- Smart and simple indicator design
- Extends network range and coverage
- Outdoor range up to 1000 m
- Supports battery input with 2 x AA Alkaline batteries

Specifications

Wireless Communication

- **IEEE Standard** IEEE 802.15.4
- **Modulation Type** DSSS (OQPSK)
- **Frequency Band** ISM 2.4 GHz (2.4 GHz ~ 2.4835 GHz)
- **Channels** 11 - 26
- **RF Data Rate** 250 Kbps
- **Transmit Power** Typ. 19 ± 1 dBm
- **Receiver Sensitivity** -97 dBm
- **Topology** Star / Tree / Mesh
- **Outdoor Range** 1000 m (with 2 dBi Antenna)
- **Function** Router

General

- **Connectors** 1 x plug-in terminal block (#14 ~ 22 AWG)
- **Power Input** Unregulated 10 ~ 30 V_{DC}
- **Battery Input** 2 x AA Alkaline
- **Power Consumption** 0.8 W @ 24 V_{DC}
0.3 W @ 3 V_{DC} (Battery AA * 2)

Common Specifications

Environment

- **Operating Temperature**
 - External Power -20°C ~ 70°C (-4°F ~ 157.9°F)
 - Battery Power 0°C ~ 50°C (32°F ~ 122°F)
- **Storage Temperature** -40°C ~ 85°C (-40°F ~ 184°F)
- **Operating Humidity** 20~95% RH
- **Storage Humidity** 0~95% RH

Ordering Information

- **ADAM-2510Z** Wireless Router Node