



METAL STRIP OPEN BARREL STAR RINGS WITH VIBRATION SUPPORT



Material	Order No.	Wire Size AWG (mm ²)	Stud Size S	Maximum Width W (in.)	Minimum Clearance C (in.)	Maximum Length L (in.)
Brass	19084-0001	14-18 (2.00-0.80)	6	.385	.275	.949
Brass	19084-0002	14-18 (2.00-0.80)	8	.385	.275	.949
Brass	19084-0003	14-18 (2.00-0.80)	10	.385	.275	.949
Tin-Plated Brass	19084-0004	14-18 (2.00-0.80)	6	.385	.275	.949
Tin-Plated Brass	19084-0005	14-18 (2.00-0.80)	8	.385	.275	.949
Tin-Plated Brass	19084-0006	14-18 (2.00-0.80)	10	.385	.275	.949
Tin-Plated Steel	19084-0007	14-18 (2.00-0.80)	6	.385	.275	.949
Tin-Plated Steel	19084-0008	14-18 (2.00-0.80)	8	.385	.275	.949
Tin-Plated Steel	19084-0009	14-18 (2.00-0.80)	10	.385	.275	.949
Tin-Plated Steel	19084-0011	24 (0.20)	10	.480	.386	.965

Note: 14-18 part will accept 12 gauge wire



METAL STRIP OPEN BARREL RINGS WITH VIBRATION SUPPORT



Material	Order No.	Wire Size AWG (mm ²)	Stud Size S	Maximum Width W (in.)	Minimum Clearance C (in.)	Maximum Length L (in.)
Brass	19085-0001	14-18 (2.00-0.80)	6	.385	.275	.949
Brass	19085-0002	14-18 (2.00-0.80)	8	.385	.275	.949
Brass	19085-0003	14-18 (2.00-0.80)	10	.385	.275	.949
Tin-Plated Brass	19085-0004	14-18 (2.00-0.80)	6	.385	.275	.949
Tin-Plated Brass	19085-0005	14-18 (2.00-0.80)	8	.385	.275	.949
Tin-Plated Brass	19085-0006	14-18 (2.00-0.80)	10	.385	.275	.949
Tin-Plated Steel	19085-0007	14-18 (2.00-0.80)	6	.385	.275	.949
Tin-Plated Steel	19085-0008	14-18 (2.00-0.80)	8	.385	.275	.949
Tin-Plated Steel	19085-0009	14-18 (2.00-0.80)	10	.385	.275	.949

Note: 14-18 part will accept 12 gauge wire

RING TONGUE (OFFSET)



Wire Range	Material: Brass or Steel			Krimtite®	
	Stud Size S	Max. Width W	Min. Clearance C	Order No.	Max. Length L
14-12 2.0-3.0mm ²	10 (-)	.425 (10.8)	.370 (9.4)	19069-0380	.804 (20.4)