

SANYO	No.2476A	2SC4169
		NPN Epitaxial Planar Silicon Transistor

Driver Applications

Applications

- Suitable for use in switching of L load (motor drivers, printer hammer drivers, relay drivers)

Features

- On-chip zener diode of $60 \pm 10V$ between collector and base
- Uniformity in collector to base voltage
- High DC current gain : $h_{FE} = 1000 \text{ min}$ ($V_{CE} = 5V, I_C = 500mA$)
- Wide ASO
- High inductive load handling capability : $Es/b = 15mJ$ (min)

Absolute Maximum Ratings at $T_a = 25^\circ C$


			unit
Collector to Base Voltage	V_{CBO}	※ 50	V
Collector to Emitter Voltage	V_{CEO}	※ 50	V
Emitter to Base Voltage	V_{EBO}	6	V
Collector Current	I_C	1.2	mA
Collector Current(Pulse)	I_{CP}	2.5	mA
Collector Dissipation	P_C	1	mW
Junction Temperature	T_j	150	$^\circ C$
Storage Temperature	T_{stg}	-55 to +150	$^\circ C$

※ : On-chip zener diode ($60 \pm 10V$)


Electrical Characteristics at $T_a = 25^\circ C$

			min	typ	max	unit
Collector Cutoff Current	I_{CBO}	$V_{CB} = 40V, I_E = 0$			10	μA
Emitter Cutoff Current	I_{EBO}	$V_{EB} = 5V, I_C = 0$			10	μA
DC Current Gain	h_{FE}	$V_{CE} = 5V, I_C = 500mA$	1000	4000		
C-E Saturation Voltage	$V_{CE(sat)}$	$I_C = 500mA, I_B = 2mA$		1.0	1.5	V
B-E Saturation Voltage	$V_{BE(sat)}$	$I_C = 500mA, I_B = 2mA$			2.0	V
Inductive Load Handling Capability	Es/b	$L = 100mH, R_{BE} = 100\Omega$	15			mJ
C-B Breakdown Voltage	$V_{(BR)CBO}$	$I_C = 100\mu A, I_E = 0$	50	60	70	V
C-E Breakdown Voltage	$V_{(BR)CEO}$	$I_C = 1mA, R_{BE} = \infty$	50	60	70	V
Turn-ON time	t_{on}	See specified Test Circuit.		0.2		μs
Storage Time	t_{stg}	Same as above.		2.2		μs
Fall Time	t_f	Same as above.		0.4		μs

Switching Time Test Circuit



Package Dimensions 2006A
(unit: mm)




EIAJ: SC-51
SANYO:MP

B: Base
C: Collector
E: Emitter







Unit(Resistance : Ω , Capacitance : F)



Es/b Test Circuit

$V_{CC} = 20V, R_{BE} = 100\Omega$



Unit(Resistance : Ω)





- No products described or contained herein are intended for use in surgical implants, life-support systems, aerospace equipment, nuclear power control systems, vehicles, disaster/crime-prevention equipment and the like, the failure of which may directly or indirectly cause injury, death or property loss.
- Anyone purchasing any products described or contained herein for an above-mentioned use shall:
 - ① Accept full responsibility and indemnify and defend SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors and all their officers and employees, jointly and severally, against any and all claims and litigation and all damages, cost and expenses associated with such use:
 - ② Not impose any responsibility for any fault or negligence which may be cited in any such claim or litigation on SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors or any of their officers and employees jointly or severally.
- Information (including circuit diagrams and circuit parameters) herein is for example only; it is not guaranteed for volume production. SANYO believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.