



1201-21-9

REVISIONS	
ISSUE	CHANGES
0	ER 35639 KVH 06/13/94
B	REVISED PER DMF304 & ER34488 KPL 08/22/11

CUSTOMER SALES DRAWING

THIS DRAWING, THE DESIGNS AND IDEAS EMBODIED IN THE DEVICE TO WHICH IT RELATES, AND THE METHOD OF PRODUCING THE DEVICE, ARE THE PROPERTY OF WINCHESTER ELECTRONICS CORPORATION AND SHALL NOT BE EMPLOYED, COPIED, OR DISCLOSED TO ANYONE, IN ANY MANNER WITHOUT THE CONSENT OF WINCHESTER ELECTRONICS CORPORATION.

SCALE 3:1

APPROX SURFACE AREA

CAGE CODE: 91836

REF: BOEING

JACK, PANEL, N

DRAWN KH DATE 05/13/94

DESIGN JT DATE 05/16/94

APPR. DATE

WINCHESTER ELECTRONICS Winchester Electronics Corporation
62 Barnes Industrial Road North
Wallingford, Connecticut 06492

1201-21-9

NOTES:

- FOR USE WITH BOEING BMS13-65 OG & ADAMS RUSSELL FC48Z CABLES.
- FOR CABLING INSTRUCTIONS SEE 3-546-2.
- FOR CRIMPING USE DIE KTH-2229.
- INTERFACE PER MIL-STD-348, FIG. 304-2.
- CONTACT (1-7311-1MA9) SUPPLIED UNASSEMBLED.
- MARK PACKAGE: KINGS 1201-21-9 (DATE CODE)
- MATERIALS:
INSULATOR: TEFLON, ASTM D1710
CENTER CONTACT: BER. COPPER, ASTM B196
K-GRIP SLEEVE: COM. BRONZE, ASTM B135
ALL OTHER METAL PARTS: BRASS, ASTM B16
- FINISHES:
CENTER CONTACT: .000050 MIN GOLD PLATE, PER ASTM B488 OVER .000050 MIN. NICKEL PER AMS-QQ-N-290 (RoHS)
ALL OTHER METAL PARTS: .000050 MIN NICKEL PER AMS-QQ-N-290 OVER .000050 MIN COPPER PER ASTM B734 (RoHS)
- ELECTRICAL CHARACTERISTICS:
NOMINAL IMPEDANCE: 50 OHMS
WORKING VOLTAGE: 1000 VRMS
FREQUENCY RANGE: DC TO 11 GHz
- WEIGHT: 51.4 GRAMS