

5991-475

# GP BATTERY PACK

## M115

### Technical Data for Cellular Phone Battery Pack NiCd

#### Specifications :

Model No	:	M115
Battery Type	:	Nickel Cadmium
For use with	:	NEC P100
Color	:	Dark Grey (DG)
Battery	:	5 X GP35AAS
Nominal Voltage	:	6.0V
Cut Off Voltage	:	5.0V
Capacity	:	850 mAh at 0.2C
Continuous Talk Time*	:	120 minutes (estimated)
Stand-by Time*	:	24 hours (estimated)
Temperature Range	:	Charge : 0 ~ 45°C Discharge : -20 ~ 50°C Storage : -20 ~ 50°C
Casing Material	:	ABS
Typical Weight	:	125g
Drawing	:	Available upon request
Charging	:	Battery should be charged in a GP or an Original Manufacturer charger. First Charge Rate : 0.1C Subsequent Charge Rate : 0.1C ~ 1C
Safety	:	Each battery is equipped with a polyswitch, thermistor and diode to protect battery from high temperature and/or short circuit. Each cell is also equipped with a safety vent system in case abuses occur.
Warranty	:	Six (6) months limited warranty from date of purchase.

\*data valid only when the battery pack is on fully charged condition.  
 NEC is a registered trademark of NEC AMERICA INC.



A product of the Gold Peak Industries Group

SYLVA PRODUCT SPEC : RWIS9704 R2

Manufacturer reserves the right to alter or amend the design, model and specification without prior notice.