



**NOTES:**

1. FOR USE WITH RG-58, 58A, 58C, 141, 141A & 303/U CABLE.
  2. FOR CABLING INSTRUCTIONS SEE CP-465.
  3. FOR CRIMPING USE DIE KTH-2001.
  4. INTERFACE PER MIL-STD-348, FIG. 301-1.
  5. CONTACT MUST BE SOLDERED ON RG-58/U BUT MAY BE CRIMPED ON BALANCE OF CABLE GROUPS.
- 6. MATERIALS:**  
 INSULATORS: TEFLON, ASTM-D1457  
 GASKET: SIL. RUB., PER A-A-59588  
 K-GRIP SLEEVE: COM. BRONZE; ASTM-B-135  
 ANGLE CONTACT } BER. COP., ASTM-B-196  
 OUTER CONTACT }  
 ALL OTHER PARTS: BRASS, ASTM-B16
- 7. FINISHES:**  
 CENTER CONTACTS: HARD GOLD P.L.T. PER ASTM-B488  
 ALL OTHER METAL PARTS: SILVER PLATE PER ASTM-B700
- 8. ELECTRICAL CHARACTERISTICS:**  
 NOMINAL IMPEDANCE: 50 OHMS  
 FREQUENCY RANGE: DC TO 4 GHz.  
 VOLTAGE RATING: 500 VRMS

PART NO. 756-21-7

REVISIONS	
ISSUE	CHANGES
C	ER 23675 JUN 04/27/10

CUSTOMER  
SALES DRAWING

SCALE	4:1
APPROX SURFACE AREA	
WAS E-20175, REPLACES KC-59-352.	
USED ON	
REF: 756-19-7	
	PLUG, ANG, BNC
	M39012/20-0006
DRAWN	HVN
DATE	03/14/03
DESIGN	HVN
DATE	03/14/03
APPR.	
DATE	

**KINGS**  
 Winchester Electronics  
 62 Service Industrial  
 Road North  
 Winchester, MA 01890

SD756-21-7