

POWER SCHOTTKY RECTIFIER

MAIN PRODUCT CHARACTERISTICS


$I_{F(AV)}$	1 A
V_{RRM}	60 V
T_j (max)	150°C
V_F (max)	0.56 V

FEATURES AND BENEFITS

- NEGLIGIBLE SWITCHING LOSSES
- LOW FORWARD VOLTAGE DROP

DESCRIPTION

Axial and Surface Mount Power Schottky rectifier suited for Switch Mode Power Supplies and high frequency DC to DC converters. Packaged in DO-41 and SMA, this device is intended for use in low voltage, high frequency inverters and small battery chargers.



ABSOLUTE RATINGS (limiting values)

Symbol	Parameter			Value	Unit		
V_{RRM}	Repetitive peak reverse voltage			60	V		
$I_{F(RMS)}$	RMS forward current			10	A		
$I_{F(AV)}$	Average forward current	$T_L = 130^\circ\text{C}$	$\delta = 0.5$	1	A		
		$T_L = 120^\circ\text{C}$	$\delta = 0.5$	DO-41			
I_{FSM}	Surge non repetitive forward current	$t_p = 10 \text{ ms}$ Sinusoidal		40	A		
T_{stg}	Storage temperature range			- 65 to + 150	°C		
T_j	Maximum junction temperature *			150	°C		
dV/dt	Critical rate of rise of reverse voltage			10000	V/μs		

* : $\frac{dP_{tot}}{dT_j} < \frac{1}{R_{th}(j - a)}$ thermal runaway condition for a diode on its own heatsink

STPS1L60/A

THERMAL RESISTANCES

Symbol	Parameter			Value	Unit
$R_{th(j-a)}$	Junction to ambient	Lead length = 10 mm	DO-41	100	$^{\circ}\text{C/W}$
			SMA	120	
$R_{th(j-l)}$	Junction to leads	Lead length = 10 mm	DO-41	45	$^{\circ}\text{C/W}$
			SMA	30	

STATIC ELECTRICAL CHARACTERISTICS

Symbol	Parameter	Tests conditions		Min.	Typ.	Max.	Unit
I_R *	Reverse leakage current	$T_j = 25^{\circ}\text{C}$	$V_R = 60\text{V}$			50	μA
		$T_j = 100^{\circ}\text{C}$			1.5	5	mA
V_F *	Forward voltage drop	$T_j = 25^{\circ}\text{C}$	$I_F = 1\text{ A}$			0.57	V
		$T_j = 100^{\circ}\text{C}$				0.56	
		$T_j = 125^{\circ}\text{C}$		0.5		0.54	
		$T_j = 25^{\circ}\text{C}$	$I_F = 2\text{ A}$			0.75	
		$T_j = 100^{\circ}\text{C}$				0.68	
		$T_j = 125^{\circ}\text{C}$		0.6		0.66	

Pulse test : * $t_p = 380 \mu\text{s}$, $\delta < 2\%$

To evaluate the maximum conduction losses use the following equation:

$$P = 0.44 \times I_{F(\text{AV})} + 0.12 \times I_F^2 (\text{RMS})$$

Fig. 1: Average forward power dissipation versus average forward current.





Fig. 3-1: Non repetitive surge peak forward current versus overload duration (maximum values) (DO-41).



2/5

Fig. 2: Average forward current versus ambient temperature ($\delta = 0.5$).




Fig. 3-2: Non repetitive surge peak forward current versus overload duration (maximum values) (SMA).




Fig. 4-1: Relative variation of thermal impedance junction to ambient versus pulse duration (DO-41).




Fig. 4-2: Relative variation of thermal impedance junction to ambient versus pulse duration (SMA).




Fig. 5: Reverse leakage current versus reverse voltage applied (typical values).




Fig. 6: Junction capacitance versus reverse voltage applied (typical values).




Fig. 7-1: Forward voltage drop versus forward current (low level, maximum values) (DO-41).





Fig. 7-2: Forward voltage drop versus forward current (high level, maximum values) (SMA).



STPS1L60/A

Fig. 8: Thermal resistance junction to ambient versus copper surface under each lead (Epoxy printed circuit board FR4, Cu: 35 μ m) (SMA).






Fig. 9: Thermal resistance versus lead length (DO-41).



PACKAGE MECHANICAL DATA SMA (JEDEC DO-214AC)


REF.	DIMENSIONS			
	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A1	1.90	2.70	0.075	0.106
A2	0.05	0.20	0.002	0.008
b	1.25	1.65	0.049	0.065
c	0.15	0.41	0.006	0.016
E	4.80	5.60	0.189	0.220
E1	3.95	4.60	0.156	0.181
D	2.25	2.95	0.089	0.116

FOOT PRINT DIMENSIONS (in millimeters)



PACKAGE MECHANICAL DATA

DO-41 plastic



REF.	DIMENSIONS			
	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A	4.07	5.20	0.160	0.205
B	2.04	2.71	0.080	0.107
C	28		1.102	

Ordering type	Marking	Package	Weight	Base qty	Delivery mode
STPS1L60	Partnumber cathode ring	DO-41	0.34g	2000	Ammopack
STPS1L60RL	Partnumber cathode ring	DO-41	0.34g	5000	Tape & Reel
STPS1L60A	GB6	SMA	0.068 g	5000	Tape & Reel

- Epoxy meets UL94,V0

Information furnished is believed to be accurate and reliable. However, STMicroelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of STMicroelectronics. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied.
STMicroelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of STMicroelectronics.

The ST logo is a registered trademark of STMicroelectronics

© 2002 STMicroelectronics - Printed in Italy - All rights reserved.

STMicroelectronics GROUP OF COMPANIES

Australia - Brazil - Canada - China - Finland - France - Germany

Hong Kong - India - Israel - Italy - Japan - Malaysia - Malta - Morocco - Singapore

Spain - Sweden - Switzerland - United Kingdom - United States.

<http://www.st.com>