

ADSL LINE TRANSFORMER
P/N: AD-2064S DATA SHEET



Bothhand USA. e-mail: sales@bothhandusa.com http://www.bothhand.com

Feature



- Recommended by Analog Devices for use with the ST Microelectronics' ASCOT Chipsets.
- Excellent THD performance.
- Small footprint.
- Operating Temperature.: -10°C to +60°C.
- Storage Temperature.: -25°C to +75°C.

Electrical Specifications @ 25°C

Part Number	Mounting	Turn Ratio (±2%) (3-8):(1-10)	OCL (uH ±5%) @ 10KHz/0.1 V	Leakage Inductance (μH Max) @ 300 KHz/1V	Longitudinal Balance (dB Min)
			(1-10),(2+9) short	(1-10),(2+9,3+8,5+6)short	(from 30KHz to 1.1MHz)
AD-2064S	SMT	1:1	1025	10.0	-45

Additional Specifications

Part Number	THD (dB Max) (@30KHz 1Vrms)	DC Resistance (Ω Max) (1-2) (9-10) (6-8) & (3-5)	Isolation Voltage (Vrms)	Insertion Loss (dB Max)		Application
				100 KHz to 1.1MHz	300 KHz	
AD-2064S	-65	0.5	1500	-1	-0.5	CPE

Schematic

Mechanical

