

		'XY' = WIRE GAUGE (AWG)									
Product Revision		Product Dimensions									
Product Name		øΑ	øB	øС	øD	øΕ	øF	L1	L2	K	AWG
		min	min	min	min	min	min	max	max	min	
D-181-3220-90/9	F										20
D-181-3222-90/9	F	5.20	4.70	4.45	3.95	4.00	1.30	17.00	21.5	150	22
D-181-3224-90/9	F	(0.205)	(0.185)	(0.175)	(0.155)	(0.160)	(0.055)	(0.670)	(0.850)	(5.900)	24
D-181-3226-90/9	F										26

MATERIALS

- 1. INSULATION SLEEVES: Heat-shrinkable, transparent blue, radiation cross-linked modified polyvinylidene fluoride.
- 2. SOLDER PREFORMS WITH FLUX:

SOLDER: TYPE Sn63 per ANSI-J-STD-006.


FLUX: TYPE ROL1 per ANSI-J-STD-004.

- 3. MELTABLE RINGS: Thermally stabilized thermoplastic. Color: gray.
- 4. GROUND LEAD: Raychem 55A0111-XY in accordance with MIL-W-22759/32, AWG XY (see table), stranded tin plated. Color: white.
- 5. GROUND LEAD: Raychem 55A0111-XY in accordance with MIL-W-22759/32, AWG XY (see table), stranded tin plated. Color: white with black strip.

APPLICATION

- 1. These parts are designed to provide an environment protected coaxial termination on cables, rated for 125°C minimum, meeting the dimensional criteria listed, and having a tin or silverplated shields.
- 2. Temperature range: -55°C to +150°C. Install using Raychem-approved convection or infrared heating tools in accordance with Raychem process standard RCPS-200-36.

For best results, prepare the cable as shown:



SolderSleeve is a trademark of Tyco Electronics Corporation.

300 Const		itutio	s Corporation n Drive, a. 94025, U.S.A.	Raychem	TITLE: COAXIAL SOLDERSLEEVE DEVICE WITH PRE-INSTALLED LEAD						
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS. INCHES DIMENSIONS ARE BETWEEN BRACKETS.						DOCUMENT NO.: D-181-32XX-90/9					
TOLERANCES: 0.00 N/A 0.0 N/A 0 N/A	ROU	ANGLES: N/A ROUGHNESS IN MICRON		drawing at any time	es the right to amend . Users should of the product for their	DATE: Jun. 23, 1	1998	DOC ISSUE:			
DRAWN BY: M. FOROND	RAWN BY: M. FORONDA			REPLACES: D18132XX	DCR NUMBER: D981031	PROD. REV.: SEE TABLE	SCALE: None	SIZE:	SHEET: 1 of 1		