



Micro Commercial Components

Micro Commercial Components
 20736 Marilla Street Chatsworth
 CA 91311
 Phone: (818) 701-4933
 Fax: (818) 701-4939

FR2504

25 Amp Fast Recovery Rectifier

Features

- High Current($I_{F(AV)}=25A$)
- Low V_F for Forward Conduction Losses
- Glass Passivated Junction
- Lead Free Finish/RoHS Compliant(Note 1) ("P" Suffix designates RoHS Compliant. See ordering information)
- Case Material: Molded Plastic. UL Flammability Classification Rating 94V-0 and MSL Rating 1
- Marking:FR2504

MAXIMUM RATINGS

Rating	Symbol	Value	Units
Peak Repetitive Reverse Voltage	V_{RRM}	400	V
Working Peak Reverse Voltage	V_{RRM}	400	V
DC Blocking Voltage	V_{DC}	400	V
Average Rectified Forward Current($T_C=100^\circ C$)	$I_{F(AV)}$	25	A
Non-Repetitive Peak Forward Surge Current	I_{FSM}	280	A
Operating Junction and Storage Temperature Range	T_J, T_{stg}	-50 to 150	$^\circ C$

THERMAL CHARACTERISTICS


Rating	Symbol	Value	Units
Thermal Resistance	R_{thJC}	1	$^\circ C/watt$
Junction To Case			

ELECTRICAL CHARACTERISTICS ($T_J = 25^\circ C$ unless otherwise noted)

Parameter	Symbol	Conditions	Typical	Max	Units
Forward voltage(Note 2)	V_F	$I_F=25A$	1.17	1.3	V
		$I_F=50A$	1.35	1.5	
Reverse Leakage Current	I_R	$V_R=400V$	--	10	μA
Reverse Recovery Time	T_{rr}	$I_F=0.5A, I_R=1.0A$ $I_{RR}=0.25A$	110	250	ns

Notes: 1. High Temperature Solder Exemption Applied, see EU Directive Annex 7.
 2. Short duration pulse to minimize self-heating

TO-220AC



DIM	INCHES		MM		NOTE
	MIN	MAX	MIN	MAX	
A	.560	.625	14.22	15.88	
B	.380	.420	9.65	10.67	
C	.100	.135	2.54	3.43	
D	.230	.270	5.84	6.86	
F	-----	.250	-----	6.35	
G	.500	.580	12.70	14.73	
H	.190	.210	4.83	5.33	
I	.020	.045	0.51	1.14	
J	.012	.025	0.30	0.64	
K	.139	.161	3.53	4.09	∅
L	.140	.190	3.56	4.83	
M	.045	.055	1.14	1.40	
N	.080	.115	2.03	2.92	

TYPICAL CHARACTERISTICS (T = 25°C unless otherwise noted)




Figure 1. Typical Forward Characteristics




Figure 2. Typical Reverse Characteristics




Figure 3. Current Derating Curves




Figure 4. Typical Capacitance



Micro Commercial Components

Ordering Information

Device	Packing
(Part Number)-BP	Bulk;1Kpcs/Box

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. *Micro Commercial Components Corp.* does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold *Micro Commercial Components Corp.* and all the companies whose products are represented on our website, harmless against all damages.

APPLICATIONS DISCLAIMER

Products offer by *Micro Commercial Components Corp.* are not intended for use in Medical, Aerospace or Military Applications.

www.mccsemi.com