

Spezifikation für Freigabe / specification for release

Kunde / customer :

Artikelnummer / part number: **7447640082**


LF



Bezeichnung : **SMD-HF-Entstördrossel WE-GF**
 description : **SMD-RF-Choke WE-GF**

DATUM / DATE : 2004-10-11

A Mechanische Abmessungen / dimensions :




	Typ / Type M	
A	2,9 ± 0,2	mm
B	3,2 ± 0,4	mm
C	2,2 ± 0,2	mm
D	0,6 ref.	mm
E	2,5 ± 0,2	mm
F	1,0	mm

B Elektrische Eigenschaften / electrical properties :

Eigenschaften / properties	Testbedingungen / test conditions		Wert / value	Einheit / unit	tol.
Induktivität / inductance	25,2 MHz	L	0,82	µH	±10%
Güte Q / Q factor	25,2 MHz	Q	30		min.
DC-Widerstand / DC-resistance		R _{DC}	0,65	Ω	max.
Nennstrom / rated current		I _{DC}	450	mA	max.
Eigenres.-Frequenz / self-res.-frequency		SRF	140	MHz	typ.

C Lötpad / soldering spec.:



D Prüfgeräte / test equipment :

HP 4291 B für/for L und/and Q
HP 4338 B für/for R_{DC}
HP 4284 A für/for I_{DC}
HP 8722 D für/for SRF

E Testbedingungen / test conditions :

Luftfeuchtigkeit / humidity: 33%
 Umgebungstemperatur / temperature: +20°C

F Werkstoffe & Zulassungen / material & approvals :

Basismaterial / base material: Ferrit / ferrite
 Anschlusspad/ Terminal: Cu/Sn
 Gehäuse/ Housing: UL94-V0

G Eigenschaften / general specifications :

Betriebstemp. / operating temperature: -40°C - + 105°C
 Umgebungstemp. / ambient temperature: -40°C - + 85°C
 It is recommended that the temperature of the part does not exceed 105°C under worst case operating conditions.

Freigabe erteilt / general release:	Kunde / customer		
		
Datum / date	Unterschrift / signature		
	Würth Elektronik		
Geprüft / checked	Kontrolliert / approved		
		
	MST	Version 4	04-10-11
	SST	Version 2	03-05-20
	MST	Version 1	02-07-31
	Name	Änderung / modification	Datum / date

This electronic component is designed and developed with the intention for use in general electronics equipments. Before incorporating the components into any equipments in the field such as aerospace, aviation, nuclear control, submarine, transportation, (automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network where higher safety and reliability are especially required or if there is possibility of direct damage or injury to human body. In addition, even electronic component in general electrical equipments, when used in electrical circuits that require high safety, reliability functions or performance, the sufficient reliability evaluation-check for the safety must be performed before use. It is essential to give consideration when to install a protective circuit at the design stage.

Würth Elektronik eiSos GmbH & Co. KG

D-74638 Waldenburg · Max-Eyth-Strasse 1 - 3 · Germany · Telefon (+49) (0) 7942 - 945 - 0 · Telefax (+49) (0) 7942 - 945 - 400
<http://www.we-online.com>