

Part Number: C1308

Revision Level: 3

Date: 11/14/2007

**5C 20 AWG 26/34 TC RUBBER OAS RUBBER**

**CONTROL CABLE**

**A. CONSTRUCTION**

Conductor: #20 AWG 26/34 Tinned Copper  
 Insulation: 0.020" Wall Rubber  
 Cable: 5 conductors @ 2.50" LHL with jute fillers & mylar wrap.  
 Braid: #36 AWG Tinned Copper  
 80% min. coverage  
 Tape: Cotton Separator  
 Jacket: 0.035" Wall Rubber - Black  
 Print Legend: *CAROL (R) C-1308A MADE IN USA*

**DIAMETERS**

0.038" nom.  
 0.080" nom.  
 0.230" nom.  
 0.250" nom.  
 0.260" nom.  
 0.330" +/- 0.017"

**B. INDUSTRY APPROVALS**

NONE

**C. ELECTRICAL PROPERTIES**

TEMPERATURE: 60 C  
 SUGGESTED WORKING VOLTAGE (Vrms): 300Vrms  
 CONDUCTOR D.C. RESISTANCE: 11.3 Ohms/1000 ft nom

**D. COLOR CODE** *(Listed as Individual Conductors or Pairs of Conductors)*

|   |       |
|---|-------|
| 1 | Black |
| 2 | White |
| 3 | Red   |
| 4 | Green |
| 5 | Blue  |