

Part Number: C1310

Revision Level: 2

Date: 11/14/2007

**6C 20 AWG 26/34 TC RUBBER OAS RUBBER**

**CONTROL CABLE**

**A. CONSTRUCTION**

**DIAMETERS**

Conductor:	#20 AWG 26/34 Tinned Copper	0.038" nom.
Insulation:	0.020" Wall Rubber	0.080" nom.
Cable:	6 conductors @ 2.50" LHL with jute fillers & mylar wrap.	0.245" nom.
Braid	#36 AWG Tinned Copper 80% min. coverage	0.255" nom.
Tape:	Cotton Separator	0.270" nom.
Jacket:	0.035" Wall Rubber - Black	0.340" +/- 0.017"
Print Legend:	<b>CAROL (R) C-1310A MADE IN USA</b>	

**B. INDUSTRY APPROVALS**

NONE

**C. ELECTRICAL PROPERTIES**

TEMPERATURE:	60C
SUGGESTED WORKING VOLTAGE (Vrms):	300Vrms
CONDUCTOR D.C. RESISTANCE:	11.3 Ohms/1000 ft nom

**D. COLOR CODE** (Listed as Individual Conductors or Pairs of Conductors)

1	Black
2	White
3	Red
4	Green
5	Blue
6	Brown