## **PNP Silicon Epitaxial Planar Transistor**

for high voltage switching and amplifier applications



1.Base 2.Collector 3.Emitter SOT-89 Plastic Package

### Absolute Maximum Ratings (T<sub>a</sub> = 25 °C)

Parameter	Symbol	Value	Unit
Collector Base Voltage	-V <sub>CBO</sub>	400	V
Collector Emitter Voltage	-V <sub>CEO</sub>	400	V
Emitter Base Voltage	-V <sub>EBO</sub>	6	V
Collector Current	-l <sub>C</sub>	300	mA
Total Power Dissipation	P <sub>tot</sub>	625	mW
Junction Temperature	T <sub>J</sub>	150	°C
Storage Temperature Range	T <sub>stg</sub>	- 55 to + 150	°C

## Characteristics at T<sub>a</sub> = 25 °C

Parameter	Symbol	Min.	Max.	Unit
DC Current Gain at - $V_{CE}$ = 10 V, - $I_{C}$ = 1 mA at - $V_{CE}$ = 10 V, - $I_{C}$ = 10 mA at - $V_{CE}$ = 10 V, - $I_{C}$ = 50 mA at - $V_{CE}$ = 10 V, - $I_{C}$ = 100 mA	h <sub>FE</sub> h <sub>FE</sub> h <sub>FE</sub>	70 80 70 60	- 300 - -	
Collector Base Cutoff Current at -V <sub>CB</sub> = 300 V	-I <sub>CBO</sub>	-	0.1	μA
Collector Emitter Cutoff Current at -V <sub>CE</sub> = 400 V	-I <sub>CES</sub>	1	1	μA
Emitter Base Cutoff Current at -V <sub>EB</sub> = 4 V	-I <sub>EBO</sub>	ı	0.1	μΑ
Collector Base Breakdown Voltage at $-I_C = 100 \mu A$	-V <sub>(BR)CBO</sub>	400	-	V
Collector Emitter Breakdown Voltage at $-I_C = 1$ mA	-V <sub>(BR)CEO</sub>	400	-	V
Emitter Base Breakdown Voltage at $-I_E = 10 \mu A$	-V <sub>(BR)EBO</sub>	6	-	V
Collector Emitter Saturation Voltage at $-I_C = 10$ mA, $-I_B = 1$ mA at $-I_C = 50$ mA, $-I_B = 5$ mA	-V <sub>CE(sat)</sub>	-	0.2 0.5	V
Base Emitter Saturation Voltage at $-I_C = 10$ mA, $-I_B = 1$ mA	-V <sub>BE(sat)</sub>	-	0.75	V
Collector Output Capacitance at -V <sub>CB</sub> = 20 V, f = 1 MHz	C <sub>ob</sub>	-	7	pF



# SEMTECH ELECTRONICS LTD.

(Subsidiary of Sino-Tech International Holdings Limited, a company listed on the Hong Kong Stock Exchange, Stock Code: 724)























### SEMTECH ELECTRONICS LTD.












#### **SOT-89 PACKAGE OUTLINE**



Dimensions in mm



