# AX61132TM

### 1U Rackmount Chassis for ATX Motherboard





## **Features**

- Supports 12" x 9.6" standard ATX MB
- Internal two SATA HDD drive bays
- Supports one PCI riser card
- Supports ATX 270W power supply



▲ Front view



▲ Rear view

#### **Specifications**

-		
Standard Color	Black	
Construction	Heavy-duty steel	
Drive Capacity	Internal 2 x SATA HDD drive bay	
Cooling	2 x 4 cm ball bearing fans (15.3 CFM/each)	
Front Panel Indicators	1 x power on/off, 1 x HDD	
Front Panel Controls	1 x power on/off	
Front Panel Connectors	N/A	
Pre-punched Panel	N/A	
System Board	12" x 9.6" standard ATX MB	

Expansion Interface	1 x PCI slot (32 bits/33 MHz)
Operating Temperature	0°C ~ 40°C (32°F ~ 104°F)Range
Dimensions	482 mm (19")(W) x 430 mm (16.9") (D) x 44 mm (1.73") (H)
Weight (net/gross)	9.8 kg (21.6 lb)/10.5 kg (23.15 lb)

#### **Power Supply Specifications**

Items	Watt		Specifications	
		Input	Output	MTBF
PS270-1U	ATX 270W (PFC)	AC 90~264V (Auto)	+5V @ 18A +12V 1 @ 16A +12V 2 @ 10A +3.3V @ 16A -12V @ 0.8A	100,000 hours

#### **Recommended MB Selections**

IMB206 with LGA1156 heatsink (manufacture option) IMB207 with LGA1156 heatsink (manufacture option) IMB208 with LGA1156 heatsink (manufacture option)

#### **Optional Items**

AX96200 1-slot PCI 32 bit riser card

AX61132TM/X270 With ATX 270W power supply

#### **Ordering Information**

Embedded MicroBoxes

Overview

Embedded

Embedded Systems for Transportation Embedded Field Controllers

> Industrial Barebone Systems

Industrial Chassis

Backplanes


Supplies

Power

Peripherals & Accessories

Appendix

#### **Dimensions**



<sup>\*</sup> All specifications and photos are subject to change without notice. © 2013 Axiomtek Co., Ltd. All rights reserved.

<sup>\*</sup>Specifications and certifications are based on options and may vary.