



SPECIFICATIONS	
IMPEDANCE	50 OHMS
FREQUENCY RANGE	800-2500 MHz
COUPLING	30dB±1.0 dB MAX.
FREQUENCY SENSITIVITY	± 0.7 dB
INSERTION LOSS	0.4 dB MAX.
DIRECTIVITY	20dB MIN.
VSWR	1.25:1 MAX.
POWER INPUT	60 WATTS
RF CONNECTORS	N FEMALE
OPERATING TEMPERATURE	-20° TO +70°C



PASTERNAK ENTERPRISES, INC.
 P.O BOX 16759, IRVINE, CA 92623
 PHONE (949) 261-1920 FAX (949) 261-7451
 WEB ADDRESS: www.pasternack.com
 E-MAIL ADDRESS: sales@pasternack.com
COAXIAL & FIBER OPTICS

DWG TITLE		DES.			
PE2237-30		N FEMALE DIRECTIONAL COUPLER, 800-2500 MHz, 30 DB			
REV. -	FSCM NO. 53919	CAD FILE 072009	SCALE N/A	SIZE A	127

NOTES:
 1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
 2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
 3. DIMENSIONS ARE IN INCHES.