

Part Number: C1700

Revision Level: 11/19/2012

2C 12AWG 65/30BC PP, PVC
COMMAND® SERIES
A. CONSTRUCTION

Conductor: 12 AWG 65/30 BC
 Insulation: .009" Wall, Polypropylene (PP)
 Cable Core: 2C @ 3.25" LHL
 Jacket: .030" Polyvinyl Chloride (PVC)
 Print Legend:

DIAMETERS

.088" nom
 .106" nom
 .212" nom
 .272" nom

**CAROL® -- C1700 -- 2C 12AWG COMMAND SERIES AUDIO CABLE (UL) E60233-8
 CL3 60C -- CSA LL69381 AWM I/II A/B 80C 600V FT4 -- ROHS -- MADE IN USA
 (Date code) (Seq Footage)**

B. INDUSTRY APPROVALS

National Electrical Code	Article 725
UL Standard 444	Type CL3
CSA International	Type AWM I/II A/B

C. ELECTRICAL PROPERTIES

Temperature:	-20°C to +80°C
Suggested Working Voltage:	600V Max
Conductor DCR:	1.61 Ohms/M' @ 20°C (nom)
Mutual Capacitance:	25.1 pF/ft @ 1kHz (nom)

D. COLOR CODE

Item	COLOR
1	BLACK
2	RED

E. CUSTOMER APPROVAL

Signature: _____
 Date: _____