

Part Number: C1702

Revision Level: 11/19/2012

**2C 14AWG 41/30BC PP, PVC****COMMAND® SERIES****A. CONSTRUCTION**

Conductor: 14 AWG 41/30 BC  
Insulation: .009" Wall, Polypropylene (PP)  
Cable Core: 2C @ 6.00" LHL  
Jacket: .030" Polyvinyl Chloride (PVC)  
Print Legend:

**CAROL® -- C1702 -- 2C 14AWG COMMAND SERIES AUDIO CABLE (UL) E60233-8  
CL3 60C -- CSA LL69381 AWM I/II A/B 80C 600V FT4 -- ROHS -- MADE IN USA  
(Date code) (Seq Footage)**

**DIAMETERS**

.071" nom  
.089" nom  
.178" nom  
.238" nom

**B. INDUSTRY APPROVALS**

|                          |                   |
|--------------------------|-------------------|
| National Electrical Code | Article 725       |
| UL Standard 444          | Type CL3          |
| CSA International        | Type AWM I/II A/B |

**C. ELECTRICAL PROPERTIES**

Temperature: -20°C to +80°C  
Suggested Working Voltage: 600V Max  
Conductor DCR: 2.56 Ohms/M' @ 20°C (nom)  
Mutual Capacitance: 23.3 pF/ft @ 1kHz (nom)

**D. COLOR CODE**

| Item | COLOR |
|------|-------|
| 1    | BLACK |
| 2    | RED   |

**E. CUSTOMER APPROVAL**

Signature: \_\_\_\_\_  
Date: \_\_\_\_\_