

VTC-6265M3, 200 W, C-Band Helix TWT

200 Watt, 5.85 - 7.10 GHz, CW traveling wave tube, periodic-permanent-magnet focused, coaxial input, waveguide output, conduction cooled.

Custom configurations are also available. These variations in the performance and configuration include: mechanical configuration, electrical and RF connections, and dual-stage depressed collector.



FEATURES

- 200 Watt
- Coaxial Input
- Waveguide Output
- Weight: 7.5 lbs. max
- Conduction Cooled

MODEL	FREQUENCY (GHZ)	POWER OUTPUT (MIN)
VTC-6265M3	5.85 - 7.10	200 W

TYPICAL OPERATING PARAMETERS

	MAXIMUM	MINIMUM	TYPICAL	UNITS
Filament Voltage:	6.6	6.0	---	Vdc
Filament Current:	5	---	---	A
Helix Voltage:	9.2	7.6	---	kVdc
Helix Current:	15	---	---	mAdc
Collector Voltage 1:	.52 Ew	.48 Ew	---	kVdc
Collector Current 1:	140	---	---	mAdc
Cathode Current:	240	---	---	mAdc
Collector Voltage 2:	.34 Ew	30 Ew	---	kVdc
Collector Current 2:	240	---	---	mAdc
Cathode Warm-up Time:	---	3	---	Minutes
Drive Power:	10	---	---	mW
Baseplate Temp:	120	---	---	°C
Prime Power:	---	---	---	Watts
Load VSWR:	1.5:1	---	---	VSWR

The values listed above represent specified limits for the product and are subject to change. The data should be used for basic information only. Formal, controlled specifications may be obtained from CPI for use in equipment design.



For information on this and other CPI products, visit our website at: www.cpii.com, or contact: CPI MPP Division, 607 Hansen Way, Palo Alto, CA 94303

TELEPHONE: 1(800) 414-8823. FAX: (650) 856-0705 | EMAIL: marketing@cpii.com