


HIGH POWER AMPLIFIER APPLICATION.

FEATURES

- Recommended for 55W Audio Frequency Amplifier Output Stage.
- Complementary to KTC5197.

MAXIMUM RATING (Ta=25°C)

CHARACTERISTIC	SYMBOL	RATING	UNIT
Collector-Base Voltage	V_{CB0}	-120	V
Collector-Emitter Voltage	V_{CE0}	-120	V
Emitter-Base Voltage	V_{EB0}	-5	V
Collector Current	I_C	-10	A
Base Current	I_B	-0.8	A
Collector Power Dissipation (Tc=25°C)	P_C	80	W
Junction Temperature	T_j	150	°C
Storage Temperature Range	T_{stg}	-55 ~ 150	°C



ELECTRICAL CHARACTERISTICS (Ta=25°C)

CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Collector Cut-off Current	I_{CB0}	$V_{CB}=-120V, I_E=0$	-	-	-5.0	μA
Emitter Cut-off Current	I_{EB0}	$V_{EB}=-5V, I_C=0$	-	-	-5.0	μA
Collector-Emitter Breakdown Voltage	$V_{(BR)CEO}$	$I_C=-50mA, I_B=0$	-120	-	-	V
DC Current Gain	h_{FE} (Note1)	$V_{CE}=-5V, I_C=-1A$	55	-	160	
	h_{FE} (2)	$V_{CE}=-5V, I_C=-4A$	35	75	-	
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	$I_C=-6A, I_B=-0.6A$	-	-0.8	-2.0	V
Base-Emitter Voltage	V_{BE}	$V_{CE}=-5V, I_C=-4A$	-	-0.97	-1.5	V
Transition Frequency	f_T	$V_{CE}=-5V, I_C=-1A$	-	30	-	MHz
Collector Output Capacitance	C_{ob}	$V_{CB}=-10V, I_E=0, f=1MHz$	-	260	-	pF

Note : h_{FE} Classification R:55~110, O:80~160.

KTA1940

