



## SPECIFICATIONS

FREQUENCY RANGE: 1 TO 2 GHz  
 NUMBER OF OUTPUT PORTS: 2  
 MINIMUM ISOLATION: 22 dB  
 MAXIMUM VSWR: 1.25  
 MAXIMUM INSERTION LOSS: .3 dB  
 MAX AMPLITUDE IMBALANCE: 0.2 dB  
 MAX PHASE IMBALANCE: 3 DEGS.  
 MAX INPUT POWER: 10W (+25 DEGS. C)



**PASTERNAK ENTERPRISES, INC.**

P.O BOX 16759, IRVINE, CA 92623  
 PHONE (949) 261-1920 FAX (949) 261-7451

WEB ADDRESS: [www.pasternack.com](http://www.pasternack.com)  
 E-MAIL ADDRESS: [sales@pasternack.com](mailto:sales@pasternack.com)

**COAXIAL & FIBER OPTICS**

DWG TITLE

**PE2011**

DES.

SMA FEMALE POWER DIVIDER FREQUENCY RANGE: 1-2 GHz 2 OUTPUT PORTS

REV. B

FSCM NO. 53919

CAD FILE 042610

SCALE N/A

SIZE A

127

NOTES:

1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
3. DIMENSIONS ARE IN INCHES.