

# POKE HOME - THRU WIRE (CONNECTS PAIRS OF WIRES)

00-9286-00X-02I-X06

2

Elco Europe (A Division of AVX Ltd) CONFIDENTIAL PROPRIETY
The document on this print and information therewith are PROPRIETY
to Elco Europe (A Division of AVX Ltd) and shall not be copied
or disclosed in whole or in part without Elco Euroipe's written consent

# PREFIX -

CODE	TYPE	DETAILS
0.0	POKE HOME	WIRE TO WIRE

# SERIES -

2

3

# NO. OF WAYS

CODE	NO. OF WAYS	DETAILS
001	I	SHEET 2
002	2	SHEET 3
003	3	SHEET 4
0 0 4	4	SHEET 5
006	6	SHEET 6
008	8	SHEET 7

# WIRE SIZE -

CODE	WIRE GAUGE	MAX. CONDUCTOR	MAX. INSULATION
021	18 TO 26 AWG	I.05mm DIAMETER 2.10mm DIAME	

# COLOUR AND APPROVAL

CODE	COLOUR	AVAILABILITY	
	WHITE	STANDARD	
9	WHITE	UL APPROVED - SPECIAL ORDER	

# PLATING OPTION

CODE	CONTACTS		
06	TIN ALL OVER		

CONTROLLED RELEASE

ELCO EUROPE LA DIVISION OF AVX. LTD.; CONFIDENTIAL PROPRIETARY
THE DRAWING ON THIS PRINT AND INFORMATION THEREWITH ARE
PROPRIETARY TO ELCO EUROPE (A DIVISION OF AVX. LTD.). AND
SHALL NOT BE USED OR DISCLOSED IN WHOLE OR IN PART
WITHOUT ELCO EUROPE'S WRITTEN CONSENT.

22	
202202	
000000	3rd ANGL
0.00 0.000	ALL DIMENS

	<b>ELCO</b>
S	© COPYRIGHT ELCO EUROPE NOT TO BE DISCLOSED OR COPIED


	SHEET I OI	F 9
N.C.H.	POKE HOME CONNECTOR - THRU WIRE	DATE  4-feb-
CV Size	Part   Number	1 1 1

#### POKE HOME I WAY - THRU WIRE - 18AWG TO 26AWG




2


3




Α



SECTION ON A-A






### PACKING DETAILS

REEL Ø	330mm
MAX REEL WIDTH	22.4mm
LEADER	500mm
TRAILER	500mm
QTY PER REEL	400







Elco Europe (A Division of AVX Ltd) CONFIDENTIAL PROPRIETY The document on this print and information therewith are PROPRIETY to Elco Europe (A Division of AVX Ltd) and shall not be copied or disclosed in whole or in part without Elco Euroipe's written consent.

1

2

3

4

NOTES:
I. I WAY WIRE TO WIRE "POKE HOME" CONNECTOR, BUTTON OPERATED.

2. WIRE SIZES 18-26AWG, MAXIMUM INSULATION DIAMETER 2.10mm.

3. SPLIT BUTTON ALLOWS THE WIRES TO BE INSERTED/WITHDRAWN INDEPENDENTLY.

4. INSULATION MATERIAL:- NYLON 46, GLASS FILLED, UL94 V-0, COLOUR SEE SHEET I.

5. CONTACT MATERIAL:- TIN PLATED COPPER ALLOY.

6. FOR FULL SPECIFICATION REFER TO ELCO SPECIFICATION 201-01-132, UL COMPONENTS REFER TO ELCO SPECIFICATION 201-01-135.

7. GENERAL TOLERANCE ±0.20mm.

8. WIRE STRIP LENGTH GUIDE, SEE SHEET 8.

9. ADHESIVE STRIP FOR PANEL MOUNTING, REFER TO SHEET 9.

10. FOR UL PRODUCT CODES UL REFERENCE E320991.

ELCO EUROPE (A DIVISION OF AVX.LTD.) CONFIDENTIAL PROPRIETARY
THE DRAWING ON THIS PRINT AND INFORMATION THEREWITH ARE
PROPRIETARY TO ELCO EUROPE (A DIVISION OF AVX.LTD.) AND
SHALL NOT BE USED OR DISCLOSED IN WHOLE OR IN PART
WITHOUT ELCO EUROPE'S RRITTEN CONSENT.

	N.C.H.	POKE HOME CONNECTOR - THRU WIRE	DATE 09-Feb-II
D	Size CV	Par1 Number 00-9286-01_000S	1 1 1

155 -10-901 Release No. History 102717 19.04.2011 19.04.2011 19.04.2011 19.04.2011 19.04.2012 19.06.2012 20.06.2012

(0)

© COPYRIGHT ELCO EUROPE NOT TO BE DISCLOSED OR COPIED WITHOUT WRITTEN PERMISSION


SHEET 2 OF 9

#### POKE HOME 2 WAY - THRU WIRE - 18AWG TO 26AWG




2


3




Α




SECTION ON A-A






#### PACKING DETAILS

REEL Ø	330mm
MAX REEL WIDTH	30.4mm
LEADER	500mm
TRAILER	500mm
QTY PER REEL	400






2

3

155

-10-901

History
History
102717
102717
19.04.2011
28.04.2011
28.04.2011
28.04.2011
30.11.2011



or disclosed in whole or in part without Elco Euroipe's written consent.

(O)

NOTES:
1. 2 WAY WIRE TO WIRE "POKE HOME" CONNECTOR, BUTTON OPERATED.

2. WIRE SIZES 18-26AWG, MAXIMUM INSULATION DIAMETER 2.10mm.

3. SPLIT BUTTON ALLOWS THE WIRES TO BE INSERTED/WITHDRAWN INDEPENDENTLY.

4. INSULATION MATERIAL:- NYLON 46, GLASS FILLED, UL94 V-0, COLOUR SEE SHEET I.

5. CONTACT MATERIAL:- TIN PLATED COPPER ALLOY.

6. FOR FULL SPECIFICATION REFER TO ELCO SPECIFICATION 201-01-132, UL COMPONENTS REFER TO ELCO SPECIFICATION 201-01-135.

7. GENERAL TOLERANCE ±0.20mm.

8. WIRE STRIP LENGTH GUIDE, SEE SHEET 8.

9. ADHESIVE STRIP FOR PANEL MOUNTING, REFER TO SHEET 9.

10. FOR UL PRODUCT CODES UL REFERENCE E320991.

ELCO EUROPE (A DIVISION OF AVX LTD.) CONFIDENTIAL PROPRIETARY
THE DRAWING ON THIS PRINT AND INFORMATION THEREWITH ARE
PROPRIETARY TO ELCO EUROPE (A DIVISION OF AVX LTD.) AND
SHALL NOT BE USED OR DISCLOSED IN WHOLE OR IN PART
WITHOUT ELCO EUROPE'S WRITTEN CONSENT.

	ELCO	N.C.H.	POKE HOME CONNECTOR
NS ES	C COPYRIGHT ELCO EUROPE NOT TO BE DISCLOSED OR COPIED WITHOUT WRITTEN PERMISSION	CV CV	Part Number

Drawn . C . H .	POKE HOME CONNECTOR - THRU WIRE	DATE 09-Feb-II
CV Size	Part Number 00-9286-01_000S	1 1 1

SHEET 3 OF 9

Α POKE HOME 3 WAY - THRU WIRE - 18AWG TO 26AWG 12.80 COMPLIANT 1 BB2 BB3 B NOTE 3 -NOTE 3 = 1 == 2 == 3 = SECTION ON A-A Ø 2.20 NOTE 2 2 2 PACKING DETAILS REEL Ø 3.30mm MAX REEL WIDTH 30.4mm LEADER 500mm AVX 9286 TRAILER 500mm THRU-WIRE QTY PER REEL 400 NOTE 8 UNREELED DIRECTION UNREELED DIRECTION 3 3 Elco Europe (A Division of AVX Ltd) CONFIDENTIAL PROPRIETY The document on this print and information therewith are PROPRIETY to Elco Europe (A Division of AVX Ltd) and shall not be copied or disclosed in whole or in part without Elco Euroipe's written consent. NOTES:
1. 3 WAY WIRE TO WIRE "POKE HOME" CONNECTOR, BUTTON OPERATED.

2. WIRE SIZES 18-26AWG, MAXIMUM INSULATION DIAMETER 2.10mm.

3. SPLIT BUTTON ALLOWS THE WIRES TO BE INSERTED/WITHDRAWN INDEPENDENTLY.

4. INSULATION MATERIAL:- NYLON 46, GLASS FILLED, UL94 V-0, COLOUR SEE SHEET I.

5. CONTACT MATERIAL:- TIN PLATED COPPER ALLOY.

6. FOR FULL SPECIFICATION REFER TO ELCO SPECIFICATION 201-01-132, UL COMPONENTS REFER TO ELCO SPECIFICATION 201-01-132UL, FOR APPLICATION NOTES REFER TO ELCO SPECIFICATION 201-01-135.

7. GENERAL TOLERANCE ±0.20mm.

8. WIRE STRIP LENGTH GUIDE, SEE SHEET 8.

9. ADHESIVE STRIP FOR PANEL MOUNTING, REFER TO SHEET 9.

10. FOR UL PRODUCT CODES UL REFERENCE E320991. 4 ELCO FUROPE LA DIVISION OF AVX. LTD.) CONFIDENTIAL PROPRIETARY
THE DRAWING ON THIS PRINT AND INFORMATION THEREWITH ARE
PROPRIETARY TO ELCO EUROPE (A DIVISION OF AVX. LTD.). AND
SHALL NOT BE USED OR DISCLOSED IN WHOLE OR IN PART
WITHOUT ELCO EUROPE'S WRITTEN CONSENT. 155 SHEET 4 OF 9 Drawn N.C.H DATE 09-Feb-1 -10-901 POKE HOME CONNECTOR Release No. History 102717 19.04.2011 19.04.2011 19.04.2011 19.04.2011 19.04.2012 19.06.2012 20.06.2012 (0)[ - THRU WIRE © COPYRIGHT ELCO EUROPE NOT TO BE DISCLOSED OR COPIED WITHOUT WRITTEN PERMISSION 1 1 00-9286-01\_000S

A


В

#### POKE HOME 4 WAY - THRU WIRE - 18AWG TO 26AWG




2


3




Α




SECTION ON A-A






#### PACKING DETAILS

REEL Ø	330mm	
MAX REEL WIDTH	38.4mm	
LEADER	500mm	
TRAILER	500mm	
QTY PER REEL	400	







Elco Europe (A Division of AVX Ltd) CONFIDENTIAL PROPRIETY The document on this print and information therewith are PROPRIETY to Elco Europe (A Division of AVX Ltd) and shall not be copied or disclosed in whole or in part without Elco Euroipe's written consent.

2

3

4

155

- NOTES:
  1 4 WAY WIRE TO WIRE "POKE HOME" CONNECTOR, BUTTON OPERATED.

  2. WIRE SIZES 18-26AWG, MAXIMUM INSULATION DIAMETER 2.10mm.

  3. SPLIT BUTTON ALLOWS THE WIRES TO BE INSERTED/WITHDRAWN INDEPENDENTLY.

  4. INSULATION MATERIAL:- NYLON 46, GLASS FILLED, UL94 V-0, COLOUR SEE SHEET I.

  5. CONTACT MATERIAL:- TIN PLATED COPPER ALLOY.

  6. FOR FULL SPECIFICATION REFER TO ELCO SPECIFICATION 201-01-132, UL COMPONENTS REFER TO ELCO SPECIFICATION 201-01-132UL. FOR APPLICATION NOTES REFER TO ELCO SPECIFICATION 201-01-135.

  7. GENERAL TOLERANCE ±0.20mm.

  8. WIRE STRIP LENGTH GUIDE, SEE SHEET 8.

  9. ADHESIVE STRIP FOR PANEL MOUNTING, REFER TO SHEET 9.

  10. FOR UL PRODUCT CODES UL REFERENCE E320991.

ELCO EUROPE (A DIVISION OF AVX.LTD.) CONFIDENTIAL PROPRIETARY
THE DRAWLING ON THIS PRINT AND INFORMATION THEREWITH ARE
PROPRIETARY TO ELCO EUROPE (A DIVISION OF AVX.LTD.) AND
SHALL NOT BE USED OR DISCLOSED IN MIGUE OR IN PART
WITHOUT ELCO EUROPE'S MRITIEN CONSETT.

LCO	N.C.H.	POKE HOME CONNECTOR - THRU WIRE	DATE 09-Feb-II
YRIGHT ELCO EUROPE E DISCLOSED OR COPIED WRITTEN PERMISSION	CV Size	Part Number 00-9286-01_000\$	1 1 1

ORM-106-01-0
Release No.
History
102717
1904-201
28.04-201
16.09-201
11.201
19.01-201
19.01-201
20.06-2012

(0)[

C COPY NOT TO BE WITHOUT

SHEET 5 OF 9


Α


### POKE HOME 6 WAY - THRU WIRE - 18AWG TO 26AWG




2


3






SECTION ON A-A






#### PACKING DETAILS

REEL Ø	330mm	
MAX REEL WIDTH	50.4mm	
LEADER	500mm	
TRAILER	500mm	
QTY PER REEL	400	







Elco Europe (A Division of AVX Ltd) CONFIDENTIAL PROPRIETY The document on this print and information therewith are PROPRIETY to Elco Europe (A Division of AVX Ltd) and shall not be copied or disclosed in whole or in part without Elco Euroipe's written consent.

1

2

3

4

155

ŋ-10-901-

- NOTES:
  1. 6 WAY WIRE TO WIRE "POKE HOME" CONNECTOR, BUTTON OPERATED.

  2. WIRE SIZES 18-26AWG, MAXIMUM INSULATION DIAMETER 2.10mm.

  3. SPLIT BUTTON ALLOWS THE WIRES TO BE INSERTED/WITHDRAWN INDEPENDENTLY.

  4. INSULATION MATERIAL:- NYLON 46, GLASS FILLED, UL94 V-0, COLOUR SEE SHEET I.

  5. CONTACT MATERIAL:- TIN PLATED COPPER ALLOY.

  6. FOR FULL SPECIFICATION REFER TO ELCO SPECIFICATION 201-01-132, UL COMPONENTS REFER TO ELCO SPECIFICATION 201-01-132UL. FOR APPLICATION NOTES REFER TO ELCO SPECIFICATION 201-01-135.

  7. GENERAL TOLERANCE ±0.20mm.

  8. WIRE STRIP LENGTH GUIDE, SEE SHEET 8.

  9. ADHESIVE STRIP FOR PANEL MOUNTING, REFER TO SHEET 9.

  10. FOR UL PRODUCT CODES UL REFERENCE E320991.

ELCO FUROPE (A DIVISION OF AVX.LTD.) CONFIDENTIAL PROPRIETARY
THE DRAWING ON THIS PRINT AND INFORMATION THEREWITH ARE
PROPRIETARY TO ELCO EUROPE (A DIVISION OF AVX.LTD.) AND
SHALL NOT BE USED OR DISCLOSED IN MIGUE OR IN PART
WITHOUT ELCO EUROPE'S WRITIEN CONSETT.

<b>ELCO</b>	N.C.H.	POKE HOME CONNECTOR - THRU WIRE	DATE 09·Feb·I
C COPYRIGHT ELCO EUROPE T TO BE DISCLOSED OR COPIED (ITHOUT WRITTEN PERMISSION	Size CV	Part Number 00-9286-01_000S	1 1


Release No. History 102717 19.04.2011 19.04.2011 19.04.2011 19.04.2011 19.04.2012 19.06.2012 20.06.2012 (0)[


SHEET 6 OF 9

Α











SECTION ON A-A







2


3

PACKING DETAILS

REEL Ø	330mm	
MAX REEL WIDTH	62.4mm	
LEADER	500mm	
TRAILER	500mm	
OTY PER REEL	400	







Elco Europe (A Division of AVX Ltd) CONFIDENTIAL PROPRIETY The document on this print and information therewith are PROPRIETY to Elco Europe (A Division of AVX Ltd) and shall not be copied or disclosed in whole or in part without Elco Euroipe's written consent.

2

3

4

155

- NOTES:
  1. 8 WAY WIRE TO WIRE "POKE HOME" CONNECTOR, BUTTON OPERATED.

  2. WIRE SIZES 18-26AWG, MAXIMUM INSULATION DIAMETER 2.10mm.

  3. SPLIT BUTTON ALLOWS THE WIRES TO BE INSERTED/WITHDRAWN INDEPENDENTLY.

  4. INSULATION MATERIAL:- NYLON 46, GLASS FILLED, UL94 V-0, COLOUR SEE SHEET I.

  5. CONTACT MATERIAL:- TIN PLATED COPPER ALLOY.

  6. FOR FULL SPECIFICATION REFER TO ELCO SPECIFICATION 201-01-132, UL COMPONENTS REFER TO ELCO SPECIFICATION NOTES REFER TO ELCO SPECIFICATION 201-01-135.

  7. GENERAL TOLERANCE ±0.20mm.

  8. WIRE STRIP LENGTH GUIDE, SEE SHEET 8.

  9. ADHESIVE STRIP FOR PANEL MOUNTING, REFER TO SHEET 9.

  10. FOR UL PRODUCT CODES UL REFERENCE E320991.

A

ELCO FUROPE (A DIVISION OF AVX.LTD.) CONFIDENTIAL PROPRIETARY
THE DRAWING ON THIS PRINT AND INFORMATION THEREWITH ARE
PROPRIETARY TO ELCO EUROPE (A DIVISION OF AVX.LTD.) AND
SHALL NOT BE USED OR DISCLOSED IN MIGUE OR IN PART
WITHOUT ELCO EUROPE'S WRITIEN CONSETT.


	N.C.H.	POKE HOME CONNECTOR - THRU WIRE	DATE 09-Feb-II
IED	Size CV	Par1 Number 00-9286-01_000S	1 1 1

ORM-106-01-0
Release No-1
1 0 2 7 1 7
19 04-201
28 04-201
19 11 201
11 1201
11 1201
13 01-201
20 06-2012

(0)[

COPYRIGHT ELCO EUROPE NOT TO BE DISCLOSED OR COPIL WITHOUT WRITTEN PERMISSION

SHEET 7 OF 9



# 80-9286-400X-00-000 ADHESIVE MOUNTING TAPE

ACCESSORY - NOT SUPPLIED WITH CONNECTORS




2


3

Elco Europe (A Division of AVX Ltd) CONFIDENTIAL PROPRIETY The document on this print and information therewith are PROPRIETY to Elco Europe (A Division of AVX Ltd) and shall not be copied or disclosed in whole or in part without Elco Euroipe's written consent.

TAPE APPLIED TO CENTRE OF BASE-



Α



DART NUMBER	DIMENSION "A"	MATCHING CONNECTORS		
PART NUMBER		00-9286-00X-021-X06 THRU WIRE	00-9286-00X-121-X06 JUNCTION BOX	
80-9286-4001-00-000	4.00	I WAY	N / A	
80-9286-4002-00-000	8.00	2 WAY	4 WAY	
80-9286-4003-00-000	12.00	3 AND 4 WAY	6 AND 8 WAY	
80-9286-4006-00-000	24.00	6 AND 8 WAY	N / A	

- NOTES:1. DOUBLE SIDED FOAM FILLED ADHESIVE TAPE.
  2. WIDTH FOR I WAY, 2 WAY, 3 WAY AND 6 WAY CONNECTORS, FOR LENGTH SEE TABLE.
  3. USED TO ADHERE A 9286 CONNECTOR TO A FLAT SURFACE.
  4. SOME SURFACES MAY REQUIRE THE USE OF A CLEANING SOLVENT TO ACHIEVE BEST RESULTS.
  5. SUPPLIED CUT TO SIZE ON A REEL ON AN OVERSIZE BACKING STRIP PARTS 400 PER REEL.

ELCO EUROPE (A DIVISION OF AVX.LTD.) CONFIDENTIAL PROPRIETARY
THE DRAWLING ON THIS PRINT AND INFORMATION THEREWITH ARE
PROPRIETARY TO ELCO EUROPE (A DIVISION OF AVX.LTD.) AND
SHALL NOT BE USED OR DISCLOSED IN MIGUE OR IN PART
WITHOUT ELCO EUROPE'S MRITIEN CONSETT.

SHEE	Τ	9 1	0 F	9

9-950-10-901 Release No. History 102717 11.11.2011 30.11.2011 08.02.2012

1

2

3

4

155

(0)[

© COPYRIGHT ELCO EUROPE NOT TO BE DISCLOSED OR COPIED WITHOUT WRITTEN PERMISSION

N.C.H.	POKE HOME CONNECTOR - THRU WIRE	DATE 08-Nov-11
CV CV	0 0 - 9 2 8 6 - 0   _ 0 0 0 S	1 1 1