




PACKAGE DIMENSIONS



DIMENSIONS IN mm
PACKAGE CODE K

ST1603A



C2079

DESCRIPTION

The TIL111 is a phototransistor-type optically coupled isolator. An infrared emitting diode manufactured from specially grown gallium arsenide is selectively coupled with an NPN silicon phototransistor. The device is supplied in a standard plastic six-pin dual-in-line package.

FEATURES

- Underwriters Laboratory (UL) recognized File #E90700

APPLICATIONS

- Power supply regulators
- Digital logic inputs
- Microprocessor inputs
- Appliance sensor systems
- Industrial controls

ABSOLUTE MAXIMUM RATINGS ($T_A=25^\circ\text{C}$ Unless Otherwise Specified)

TOTAL PACKAGE

Storage temperature	-55°C to 150°C
Operating temperature	-55°C to 100°C
Lead temperature	
(soldering, 10 sec)	260°C
Total package power dissipation at 25°C	
(LED plus detector)	260 mW
Derate linearly from 25°C	3.3 mW/ $^\circ\text{C}$

INPUT DIODE

Forward DC current	100 mA
Reverse voltage	3 V
Peak forward current	
(1 μs pulse, 300 pps)	3.0 A
Power dissipation 25°C ambient	150 mW
Derate linearly from 25°C	2 mW/ $^\circ\text{C}$

OUTPUT TRANSISTOR

Power dissipation at 25°C	150 mW
Derate linearly from 25°C	2 mW/ $^\circ\text{C}$
V_{CEO}	30 V
V_{CBO}	70 V
V_{ECO}	7 V
Collector current (continuous)	100 mA

ELECTRICAL CHARACTERISTICS (At 25°C Free-Air Temperature)

INDIVIDUAL COMPONENT CHARACTERISTICS

PARAMETER	SYMBOL	TIL111			UNIT	TEST CONDITIONS
		MIN.	TYP.	MAX.		
INPUT DIODE Input diode static reverse current	I_R			10	μA	$V_R = 3\text{ V}$
Input diode static forward voltage	V_F		1.2	1.4	V	$I_F = 16\text{ mA}$
OUTPUT TRANSISTOR Collector-base breakdown voltage	$V_{(BR)CBO}$	70			V	$I_C = 10\ \mu\text{A}$, $I_E = 0$, $I_F = 0$
Collector-emitter breakdown voltage	$V_{(BR)CEO}$	30			V	$I_C = 1\text{ mA}$, $I_B = 0$, $I_F = 0$
Emitter-base breakdown voltage	$V_{(BR)EBO}$	7			V	$I_E = 10\ \mu\text{A}$, $I_C = 0$, $I_F = 0$
Transistor static forward current transfer ratio	h_{FE}	100	300			$V_{CE} = 5\text{ V}$, $I_C = 10\text{ mA}$, $I_F = 0$

TRANSFER CHARACTERISTICS

PARAMETER	SYMBOL	TIL111			UNIT	TEST CONDITIONS	
		MIN.	TYP.	MAX.			
On-state collector current	Phototransistor operation	$I_{C(on)}$	2	7	mA	$V_{CE} = 0.4\text{ V}$, $I_F = 16\text{ mA}$, $I_B = 0$	
	Photodiode operation	$I_{C(on)}$	7	20	μA	$V_{CB} = 0.4\text{ V}$, $I_C = 16\text{ mA}$, $I_E = 0$	
Off-state collector current	Phototransistor operation	$I_{C(off)}$		1	50	nA	$V_{CE} = 10\text{ V}$, $I_C = 0$, $I_B = 0$
	Photodiode operation	$I_{C(off)}$		0.1	20		$V_{CB} = 10\text{ V}$, $I_C = 0$, $I_E = 0$
Collector-emitter saturation voltage	$V_{CE(sat)}$		0.25	0.4	V	$I_C = 2\text{ mA}$, $I_F = 16\text{ mA}$, $I_B = 0$	

SWITCHING CHARACTERISTICS (At 25°C Free-Air Temperature)

PARAMETER	SYMBOL	TIL111			UNIT	TEST CONDITIONS
		MIN.	TYP.	MAX.		
Rise time	Phototransistor operation	t_r	5	10	μs	$V_{CC} = 10\text{ V}$, $I_{C(on)} = 2\text{ mA}$, $R_L = 100\ \Omega$
Fall time						
Rise time	Photodiode operation	t_r	1		μs	$V_{CC} = 10\text{ V}$, $I_{C(on)} = 20\ \mu\text{A}$, $R_L = 1\text{ k}\Omega$
Fall time						

ISOLATION CHARACTERISTICS

PARAMETER	SYMBOL	TIL111			UNIT	TEST CONDITIONS
		MIN.	TYP.	MAX.		
Input-to-output internal resistance	r_{io}	10^{11}			Ω	$V_{ISO} = \pm 1.5\text{ kV}$
Input-to-output capacitance	C_{io}		1	1.3	pF	$V_{in-out} = 0$, $f = 1\text{ MHz}$, See Note 6
Isolation voltage	V_{iso}	7500			VAC-PEAK	$I_{i.o} \leq 1\ \mu\text{A}$, 1 minute
		5300			VAC-RMS	$I_{i.o} \leq 1\ \mu\text{A}$, 1 minute




Fig. 1. Forward Voltage vs. Current

C1686




Fig. 2. Normalized CTR vs. Forward Current

C1679




Fig. 3. Normalized CTR vs. Temperature

C1680




Fig. 4. Collector Current vs. Forward Current

C1243




Fig. 5. CTR vs. RBE (Unsaturated)

C1681




Fig. 6. CTR vs. RBE (Saturated)

C1682




Fig. 7. Normalized T_{OFF} vs. RBE




Fig. 8. Normalized T_{ON} vs. RBE




Fig. 9. Switching Time vs. I_C




Fig. 10. Switching Time Test Circuit




Fig. 11. Switching Time Waveforms



PHOTOTRANSISTOR OPTOISOLATOR

DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.