

Part Number: C1228A

Revision: 1/8/2013

2C 24ga Polypropylene, Shielded, PVC

AUDIO/VIDEO AND HOME ENTERTAINMENT

A. CONSTRUCTION

Conductor: #24 AWG (19/36) Tinned Copper
 Insulation: .008" Wall, Polypropylene (PP)
 Pair: 2C @ 1.50" LHL
 Shield: Conductive Tape
 Aluminum/Polyester Tape, foil in, in contact with drain.
 Drain Wire: #24 AWG (7/32) Tinned Copper
 Jacket: .021" Wall, Polyvinyl Chloride (PVC)
 Print Legend: **CAROL C1228A MADE IN USA**

DIAMETERS

.025" Nom
 .041" Nom
 .093" Nom
 .135" Nom

B. INDUSTRY APPROVALS

C. ELECTRICAL PROPERTIES

Temperature: -20°C to +75°C
 Suggested Working Voltage: 300V Max
 Conductor DCR: 23 Ohms/1000 ft @ 20°C (nom)
 Shield Resistance: 27 Ohms/1000 ft @ 20°C (nom)
 Mutual Capacitance: 27pF/ft @ 1kHz (nom)
 Ground Capacitance: 48 pF/ft @ 1kHz (nom)

D. COLOR CODE

ITEM	COLOR
1	BLACK
2	RED

E. CUSTOMER APPROVAL

Signature: _____
 Date: _____