

SMC Plug Bulkhead Connector Solder Attachment Solder Cup Terminal, .177 inch D Hole



TECHNICAL DATA SHEET

PE4289

SMC Plug Bulkhead Connector Solder Attachment Solder Cup Terminal, .177 inch D Hole

Configuration

Connector SMC Plug
Connector Specification MIL-STD-348A
Connector Interface Type Solder Cup
Cable Attachment Method (Shield/Contact) Solder
Body Style Straight
Mount Method Bulkhead

Electrical Specifications

Impedance, Ohms 50

Mechanical Specifications

Size

 Length, in [mm]
 0.613 [15.57]

 Width/Dia., in [mm]
 0.25 [6]

 Weight, lbs [g]
 0.006 [2.72]

Connector

Type SMC Plug
Contact Material and Plating Beryllium Copper, Gold
Contact Plating Specification 30µ in. minimum
Coupling Nut Material and Plating Brass, Nickel
Coupling Nut Plating Specification 100µ in. minimum

Hex Size, in. 1/4
Torque, in-lbs [Nm] 3 [0.34]
Body Material and Plating Brass, Nickel
Body Plating Specification 100µ in. minimum

Dielectric Type Teflor

Compliance Certifications (visit www.Pasternack.com for current document)
RoHS Compliant
Yes

Plotted and Other Data

Notes: Values at 25 °C, sea level

URL: http://www.pasternack.com/smc-plug-standard-solder-cup-terminal-connector-pe4289-p.aspx

SMC Plug Bulkhead Connector Solder Attachment Solder Cup Terminal, .177 inch D Hole from Pasternack Enterprises has same day shipment for domestic and International orders. We maintain 99% availability of the industry's broadest selection of RF, microwave and fiber optic products.

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

ISO 9001 : 2008 Registered

