


NPN COMPLEMENTARY SILICON TRANSISTOR

**CIL2383
(BPL)
TO-92
BCE**



Vertical Deflection Output & Class B Sound Output Applications of Colour T.V

ABSOLUTE MAXIMUM RATINGS(Ta=25deg C unless otherwise specified)

DESCRIPTION	SYMBOL	VALUE	UNIT
Collector -Base Voltage	VCBO	180	V
Collector -Emitter Voltage	VCEO	180	V
Emitter Base Voltage	VEBO	6.0	V
Collector Current	IC	1.0	A
Peak	ICP	1.5	A
Base Current	IB	500	mA
Power Dissipation	PD	900	mW
Operating And Storage Junction Temperature Range	Tj, Tstg	-55 to +150	deg C

ELECTRICAL CHARACTERISTICS (Ta=25 deg C Unless Otherwise Specified)

DESCRIPTION	SYMBOL	TEST CONDITION	MIN	TYP	MAX	UNIT
Collector -Emitter Voltage	VCEO	IC=10mA, IB=0	180	-	-	V
Collector Cut off Current	ICBO	VCB=150V, IE=0	-	-	1.0	uA
Emitter Cut off Current	IEBO	VEB=6V, IC=0	-	-	1.0	uA
DC Current Gain	hFE*	IC=200mA, VCE=5V	60	-	320	
Collector Emitter Saturation Voltage	VCE(Sat) *	IC=500mA, IB=50mA	-	-	1.5	V
Base Emitter on Voltage	VBE(on)*	IC=5mA, VCE=5V	0.45	-	0.75	V

Dynamic Characteristics

Output Capacitance	Cob	VCB=10V, IE=0, f=1MHz	-	-	20	pF
Gain Bandwidth Product	ft	VCE=5V, IC=200mA,	20	100	-	MHz

CLASSIFICATION

	R	O	Y
hFE *	60-120	100-200	160-320

*Pulse Test : Pulse Width =300us, Duty Cycle=2%

Notes

Disclaimer

The product information and the selection guides facilitate selection of the CDIL's Discrete Semiconductor Device(s) best suited for application in your product(s) as per your requirement. It is recommended that you completely review our Data Sheet(s) so as to confirm that the Device(s) meet functionality parameters for your application. The information furnished on the CDIL Web Site/CD is believed to be accurate and reliable. CDIL however, does not assume responsibility for inaccuracies or incomplete information. Furthermore, CDIL does not assume liability whatsoever, arising out of the application or use of any CDIL product; neither does it convey any license under its patent rights nor rights of others. These products are not designed for use in life saving/support appliances or systems. CDIL customers selling these products (either as individual Discrete Semiconductor Devices or incorporated in their end products), in any life saving/support appliances or systems or applications do so at their own risk and CDIL will not be responsible for any damages resulting from such sale(s).

CDIL strives for continuous improvement and reserves the right to change the specifications of its products without prior notice.



CDIL is a registered Trademark of

Continental Device India Limited

C-120 Naraina Industrial Area, New Delhi 110 028, India.

Telephone + 91-11-579 6150 Fax + 91-11-579 9569, 579 5290

e-mail sales@cdil.com www.cdil.com