

FME Jack to BNC Male Adapter



TECHNICAL DATA SHEET

PE9711

FME Jack to BNC Male Adapter

Configuration

Connector 1 FME Jack
Impedance 1 50 Ohms
Connector 2 BNC Male
Impedance 2 50 Ohms
Connector Specification 2 MIL-STD-348A
Adapter Design Standard
Body Style Straight

Mechanical Specifications

Size

Length, in [mm] 1.285 [32.64] Width/Dia., in [mm] 0.57 [14.48]

Connector 1

Type FME Jack
Inner Conductor Material and Plating Brass, Gold
Inner Conductor Plating Specification 30μ in. minimum
Body Material and Plating Brass, Nickel
Body Plating Specification 100μ in. minimum
Dielectric Type Teflon

Connector 2

BNC Male Type Inner Conductor Material and Plating Brass, Gold Inner Conductor Plating Specification 30_u in. minimum Coupling Nut Material and Plating Brass, Nickel 100µ in. minimum Coupling Nut Plating Specification Body Material and Plating Brass, Nickel **Body Plating Specification** 100µ in. minimum Dielectric Type Teflon

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant Yes

Plotted and Other Data

Notes: Values at 25 °C, sea level

URL: http://www.pasternack.com/fme-jack-bnc-male-straight-adapter-pe9711-p.aspx

FME Jack to BNC Male Adapter from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

ISO 9001 : 2008 Registered

PE9711 CAD Drawing FME Jack to BNC Male Adapter

