

Micro Commercial Components




Micro Commercial Components 20736 Marilla Street Chatsworth CA 91311

Phone: (818) 701-4933 Fax: (818) 701-4939

MMBD4448DW

Features

- For General Purpose Switching Applications
- Lead Free Finish/Rohs Compliant ("P"Suffix designates RoHS Compliant. See ordering information)
- Ultra-Small Surface Mount Package
- High Conductance, Power Dissipation
- Fast Switching Speed
- Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1



Maximum Ratings


Symbol	Rating	Rating	Unit	
V_{RM}	Non-Repetitive Peak Reverse Voltage	100	V	
V_{RRM}	Peak Repetitive Reverse Voltage			
V_{RWM}	Working Peak Reverse Voltage	75 V		
V_R	DC Blocking Voltage			
$V_{R(RMS)}$	RMS Reverse Voltage	oltage 53		
I _{FM}	Forward Continuous Current	500	mA	
Io	Average Rectified Output Current	250	mA	
I _{FSM}	Peak Forward Surge Current @1.0 μ s	4.0	Α	
	@1.0s	2.0	A	
R _{B JA}	Thermal Resistance Junction to Ambient	625	°C/W	
P _D	Power dissipation	200	mW	
TJ	Junction Temperature	150	°C	
T _{STG}	Storage Temperature	-65 to +150	$^{\circ}\!\mathbb{C}$	

Electrical Characteristics @ 25°C Unless Otherwise Specified

Symbol	Parameter	Min	Max	Test Conditions
$V_{(BR)}$	Reverse Breakdown Voltage	75V		I _R =10 μ A
I _R	Reverse Voltage Leakage Current		2.5 μ A 50 μ A 35 μ A 25nA	V _R =75V V _R =75V, T _J =150°C V _R =25V, T _J =150°C V _R =20V
V _F	Forward Voltage	0.6 	0.72V 0.855V 1.0V 1.25V	$I_F=5.0$ mA $I_F=10$ mA $I_F=50$ mA $I_F=150$ mA
Ст	Total Capacitance		4.0pF	V _R =0V, f=1MHZ
t _{rr}	Reverse Recovery Time		4.0ns	$I_R==I_F=10\text{mA},$ $Irr=0.1xI_R,$ $R_L=100 \Omega$

200mW Switching Diodes

SOT-363





DIMENSIONS						
	INCHES		INCHES MM		М	
DIM	MIN	MAX	MIN	MAX	NOTE	
Α	.006	.014	0.15	0.35		
В	.045	.053	1.15	1.35		
С	.085	.096	2.15	2.45		
D	.026		0.65Nominal			
G	.047	.055	1.20	1.40		
Н	.071	.087	1.80	2.20		
J		.004		0.10		
K	.035	.043	0.90	1.10		
L	.010	.018	0.26	0.46		
M	003	006	0.08	0.15		


MMBD4448DW





Micro Commercial Components











T_A, AMBIENT TEMPERATURE (°C)
Fig. 4 Power Derating Curve, Total Package



Micro Commercial Components

Ordering Information:

Device	Packing
Part Number-TP	Tape&Reel: 3Kpcs/Reel

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. **Micro Commercial Components Corp.** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp.** and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.