

Part Number: C4062A

Revision Date: 12/12/2012

**3C 22 AWG 7/30 TC PVC / PVC**
**COMMUNICATION & CONTROL CABLE**
**A. CONSTRUCTION**

Conductor: #22 AWG 7/30 Tinned Copper  
 Insulation: .010" Polyvinyl Chloride (PVC)  
 Cable Core: Cable 3/C @ 1.50" LHL  
 Jacket: .032" Polyvinyl Chloride (PVC) jacket

**DIAMETERS**

.029" Nom  
 .049" Nom  
 .167" Nom

Print Legend: **CAROL (R) 22 AWG -- C4062A-- 75C E105765-H CM (UL)  
 C(UL) OR AWM STYLE 2464/2576 --- CSA LL69381 CMG  
 60C -- MADE IN USA (PRINT EVERY 2 FT) (DATE CODE)**

**B. INDUSTRY APPROVALS**

UL Standard 758	AWM Style 2464 / 2576
National Electrical Code	Article 800
UL Standard 444	Type CM
CSA International	Type CMG

**C. ELECTRICAL PROPERTIES**

Temperature: -20°C to +80°C  
 Suggested Working Voltage: 300V  
 Conductor DCR: 16.89 Ohms/M' @ 20°C (Max)  
 Mutual Capacitance: 24.5 pF/ft. @ 1 kHz (Nom)

**D. COLOR CODE**

ITEM	COLOR
1	BLACK
2	RED
3	LT GRN

**E. CUSTOMER APPROVAL**

Signature: \_\_\_\_\_  
 Date: \_\_\_\_\_