

Part Number: C4063A

Revision Date: 10/9/2012

**4C 22 AWG 7/30 TC PVC / PVC**

**COMMUNICATION & CONTROL CABLE**

**A. CONSTRUCTION**

Conductor: #22 AWG 7/30 Tinned Copper  
 Insulation: .010" Polyvinyl Chloride (PVC)  
 Cable Core: Cable 4/C @ 4.00" LHL  
 Jacket: .032" Polyvinyl Chloride (PVC) jacket

**DIAMETERS**

.029" Nom  
 .049" Nom  
 .189" Nom

Print Legend: **CAROL (R) 22 AWG -- C4063A-- 75C E105765-H CM (UL)  
 C(UL) OR AWM STYLE 2464/2576 --- CSA LL69381 CMG  
 60C -- MADE IN USA (PRINT EVERY 2 FT) (DATE CODE)**

**B. INDUSTRY APPROVALS**

UL Standard 758	AWM Style 2464 / 2576
UL Standard 800	CM
CSA International	Type CMG
UL	SUNLIGHT RESISTANT (720 HOUR)

**C. ELECTRICAL PROPERTIES**

Temperature: CMG: 60C, AWM: 80C, CM: 75C  
 Suggested Working Voltage: 300V  
 Conductor DCR: 16.89 Ohms/M' @ 20°C

**D. COLOR CODE**

ITEM	COLOR
1	BLACK
2	WHT
3	RED
4	LT GRN