



# SPECIFICATIONS

FREQUENCY RANGE: 1 TO 2 GHz  
 ISOLATION: 18  
 LOSS (dB) MIN: 0.6  
 VSWR MAX: 1.35:1  
 FORWARD POWER: 10 WATT  
 REVERSE POWER: 10 WATT  
 INPUT CONNECTOR: N TYPE  
 OUTPUT CONNECTOR: N TYPE



**PASTERNAK ENTERPRISES, INC.**

P.O BOX 16759, IRVINE, CA 92623  
 PHONE (949) 261-1920 FAX (949) 261-7451

WEB ADDRESS: [www.pasternack.com](http://www.pasternack.com)  
 E-MAIL ADDRESS: [sales@pasternack.com](mailto:sales@pasternack.com)

**COAXIAL & FIBER OPTICS**

DWG TITLE

**PE8310**

DES. N FEMALE ISOLATOR, 1-2 GHz, 10W

REV. A **FSCM NO. 53919**

CAD FILE 011508

SCALE N/A

SIZE A 127

**NOTES:**

1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
3. DIMENSIONS ARE IN INCHES.