


# UPS-BAT/VRLA/24DC/ 1.3AH

Order No.: 2320296

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2320296>

Rechargeable battery module, lead AGM, VRLA technology, 24 V DC, 1.3 Ah, tool-free battery replacement, automatic detection and communication with QUINT UPS-IQ



Commercial data	
GTIN (EAN)	 4 046356 554176
sales group	H061
Pack	1 pcs.
Customs tariff	85072080
Catalog page information	Page 618 (IF-2011)

<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data	
<b>Input data</b>	
Nominal input voltage	24 V DC
Buffer period	20 min (2 A) 5 min (5 A)
<b>Output data</b>	
Output current	max. 15 A
Connection in parallel	15
Connection in series	No
Output fuse	1x 15 A

**General data**

IQ technology	Yes
Disposal	Used batteries must not be thrown away with household waste, they should instead be disposed of in accordance with applicable national regulations. They can also be returned to Phoenix Contact or the manufacturer.
Width	54 mm
Height	157 mm
Depth	113 mm
Net weight	1.7 kg
Memory medium	1.3 Ah battery
Degree of protection	IP20
Protection class	III
Ambient temperature (operation)	0 °C ... 40 °C
Ambient temperature (storage/transport)	0 °C ... 40 °C
Max. permissible relative humidity (operation)	95 %
Mounting position	horizontal DIN rail NS 35, EN 60715
Standard - Electrical safety	EN 60950-1/VDE 0805 (SELV) EN 61558-2-17
Standard – Electronic equipment for use in electrical power installations and their assembly into electrical power installations	EN 50178/VDE 0160 (PELV)
UL approvals	UL/C-UL listed UL 508 UL/C-UL Recognized UL 60950 UL/C-UL Listed UL 1604 Class I, Division 2, Groups A, B, C, D UL listed ANSI/ISA-12.12.01 class I, division 2, groups A, B, C, D UL/C-UL Recognized UL 1778
VdS approval	G 196049

**Certificates / Approvals**

Certification	CUL
Certifications applied for:	UL Listed / CUL Listed / UL / UL-EX

### Accessories


Item	Designation	Description
<b>Fuse</b>		
0913676	SI FORM C 15 A DIN 72581	Flat-type plug-in fuse, type C, color code: light blue, nominal current: 15 A

### General

2853983	UTA 107	Universal DIN rail adapter, for screwing on switchgear
---------	---------	--

### Diagrams/Drawings

Block diagram



**Address**

PHOENIX CONTACT Inc., USA  
586 Fulling Mill Road  
Middletown, PA 17057, USA  
Phone (800) 888-7388  
Fax (717) 944-1625  
<http://www.phoenixcon.com>



© 2011 Phoenix Contact  
Technical modifications reserved;