

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [54434-0608](#)
Status: **Active**
Description: 0.50mm Pitch SlimStack™ Receptacle, Surface Mount, Dual Row, Vertical, 5.60mm Stacking Heights, with Solder Tabs, 60 Circuits, Lead-Free

Documents:

[3D Model](#) [Product Specification PS-54434-011 \(PDF\)](#)
[Drawing \(PDF\)](#) [RoHS Certificate of Compliance \(PDF\)](#)

General

Product Family	PCB Receptacles
Series	54434
Application	Board-to-Board, Signal
Product Name	SlimStack™
UPC	822348131006

Physical

Circuits (Loaded)	60
Circuits (maximum)	60
Durability (mating cycles max)	30
Glow-Wire Compliant	No
Lock to Mating Part	Yes
Mated Height	5.60mm
Material - Plating Mating	Gold
Material - Plating Termination	Gold
Net Weight	286.060/mg
Number of Rows	2
Orientation	Vertical
PCB Locator	No
PCB Retention	Yes
PCB Thickness - Recommended	1.60mm
Packaging Type	Embossed Tape on Reel
Pitch - Mating Interface	0.50mm
Plating min - Mating	0.102µm
Plating min - Termination	0.102µm
Polarized to PCB	No
Surface Mount Compatible (SMC)	N/A
Temperature Range - Operating	-25°C to +85°C
Termination Interface: Style	Surface Mount


Electrical

Current - Maximum per Contact	0.5A
Voltage - Maximum	50V

Material Info

Reference - Drawing Numbers

Product Specification	PS-54434-011, RPS-54434-012, RPS-54434-013
Sales Drawing	SD-54434-009, SD-54434-010



EU RoHS

ELV and RoHS Compliant
REACH SVHC
Contains SVHC: Yes
 1-bromopropane
Low-Halogen Status
Not Low-Halogen

China RoHS



Need more information on product environmental compliance?

Email productcompliance@molex.com
 For a multiple part number RoHS Certificate of Compliance, [click here](#)

Please visit the [Contact Us](#) section for any non-product compliance questions.

Search Parts in this Series

[54434Series](#)

Mates With

[55289](#)