

General Cable Product Data Sheet

Part Number: C3106

Revision Level: 0

Date: 7/7/2007

4C 22 7/30 TC FLEX PVDF

TYPE CL2P

A. CONSTRUCTION

Conductor: #22 AWG 7/30 Tinned Copper
Insulation: 0.006" Wall FLEXGUARD*
Cable: 4 Conductors @ 4.00" LHL.
Jacket: 0.010" Wall PVDF – Natural
-Plenum ripcord under jacket.

DIAMETERS

0.030" nom.
0.042" nom.
0.101" nom.
0.121" +/- 0.006"

Print Legend: **CAROL (R) - - 22 AWG - - 60C E63869-S CL2P (UL) - - MADE IN USA**
DATE CODE (PRINT EVERY 2 FT)

B. INDUSTRY APPROVALS

National Electrical Code
UL Standard 13

Article 725
Type CL2P

C. ELECTRICAL PROPERTIES

TEMPERATURE: 60C
SUGGESTED WORKING VOLTAGE (Vrms): 150 Vrms (CL2P)
CONDUCTOR D.C. RESISTANCE: 16.6 Ohms/1000 ft. nom. @ 20C

D. COLOR CODE (Listed as Individual Conductors or Pairs of Conductors)

1	Black
2	White
3	Red
4	Green

Note: Data are subject to change without notice. Contact your Customer Service representative for latest information.

*FLEXGUARD is a trademark of General Cable Corporation for polymer alloy insulation and jackets.