

Linear Systems replaces discontinued Siliconix U404 with LSU404

The U404/ LSU404 is a Low Noise, Low Drift, Monolithic Dual N-Channel JFET

The LSU404 is a high-performance monolithic dual JFET featuring extremely low noise, tight offset voltage and low drift over temperature specifications, and is targeted for use in a wide range of precision instrumentation applications. The LSU404 features a 5-mV offset and 10- $\mu\text{V}/^\circ\text{C}$ drift. The LSU404 is a direct replacement for discontinued Siliconix U404.

The hermetically sealed TO-71 & TO-78 packages are well suited for military applications.

(See Packaging Information).

U404 / LSU404 Applications:

- Wideband Differential Amps
- High-Speed, Temp-Compensated Single-Ended Input Amps
- High-Speed Comparators
- Impedance Converters and vibrations detectors.

FEATURES

LOW DRIFT | V_{GS1-2}/T | = 10 $\mu\text{V}/^\circ\text{C}$ TYP.

LOW NOISE e_n = 6nV/Hz @ 10Hz TYP.

LOW PINCHOFF V_p = 2.5V TYP.

ABSOLUTE MAXIMUM RATINGS @ 25°C (unless otherwise noted)

Maximum Temperatures

Storage Temperature -65°C to +150°C

Operating Junction Temperature +150°C

Maximum Voltage and Current for Each Transistor – Note 1

- V_{GSS} Gate Voltage to Drain or Source 50V

- V_{DSO} Drain to Source Voltage 50V

- $I_{G(f)}$ Gate Forward Current 10mA

Maximum Power Dissipation

Device Dissipation @ Free Air – Total 300mW

MATCHING CHARACTERISTICS @ 25°C UNLESS OTHERWISE NOTED

SYMBOL	CHARACTERISTICS	VALUE	UNITS	CONDITIONS
V_{GS1-2}/T max.	DRIFT VS. TEMPERATURE	25	$\mu\text{V}/^\circ\text{C}$	$V_{DG}=10\text{V}$, $I_D=200\mu\text{A}$ $T_A=-55^\circ\text{C}$ to +125°C
V_{GS1-2} max.	OFFSET VOLTAGE	15	mV	$V_{DG}=10\text{V}$, $I_D=200\mu\text{A}$

ELECTRICAL CHARACTERISTICS @ 25°C (unless otherwise noted)


SYMBOL	CHARACTERISTICS	MIN.	TYP.	MAX.	UNITS	CONDITIONS
BV_{GSS}	Breakdown Voltage	50	60	--	V	$V_{DS} = 0$ $I_D = 1\text{nA}$
BV_{GGO}	Gate-To-Gate Breakdown	± 50	--	--	V	$I_G = 1\text{nA}$ $I_D = 0$ $I_S = 0$
TRANSCONDUCTANCE						
Y_{fSS}	Full Conduction	2000	--	7000	μmho	$V_{DG} = 10\text{V}$ $V_{GS} = 0\text{V}$ $f = 1\text{kHz}$
Y_{fS}	Typical Operation	1000	--	2000	μmho	$V_{DG} = 15\text{V}$ $I_D = 200\mu\text{A}$ $f = 1\text{kHz}$
Y_{fS1-2}/Y_{fS}	Mismatch	--	0.6	3	%	
DRAIN CURRENT						
I_{DSS}	Full Conduction	0.5	--	10	mA	$V_{DG} = 10\text{V}$ $V_{GS} = 0\text{V}$
I_{DSS1-2}/I_{DSS}	Mismatch at Full Conduction	--	1	5	%	
GATE VOLTAGE						
$V_{GS(off)}$ or V_p	Pinchoff voltage	-0.5	--	-2.5	V	$V_{DS} = 15\text{V}$ $I_D = 1\text{nA}$
$V_{GS(on)}$	Operating Range	--	--	-2.3	V	$V_{DS} = 15\text{V}$ $I_D = 200\mu\text{A}$
GATE CURRENT						
- $I_{Gmax.}$	Operating	--	-4	-15	pA	$V_{DG} = 15\text{V}$ $I_D = 200\mu\text{A}$
- $I_{Gmax.}$	High Temperature	--	--	-10	nA	$T_A = +125^\circ\text{C}$
- $I_{GSSmax.}$	At Full Conduction	--	--	100	pA	$V_{DS} = 0$
- $I_{GSSmax.}$	High Temperature	5	5	5	pA	$V_{DG} = 15\text{V}$ $T_A = +125^\circ\text{C}$
OUTPUT CONDUCTANCE						
Y_{OSS}	Full Conduction	--	--	20	μmho	$V_{DG} = 10\text{V}$ $V_{GS} = 0\text{V}$
Y_{OS}	Operating	--	0.2	2	μmho	$V_{DG} = 15\text{V}$ $I_D = 500\mu\text{A}$
COMMON MODE REJECTION						
CMR	$-20 \log V_{GS1-2}/V_{DS} $	95	--	--	dB	$V_{DS} = 10$ to 20V $I_D = 30\mu\text{A}$
NOISE						
NF	Figure	--	--	0.5	dB	$V_{DS} = 15\text{V}$ $V_{GS} = 0\text{V}$ $R_G = 10\text{M}$ $f = 100\text{Hz}$ $\text{NBW} = 6\text{Hz}$
e_n	Voltage	--	20	--	nV/ $\sqrt{\text{Hz}}$	$V_{DS} = 15\text{V}$ $I_D = 200\mu\text{A}$ $f = 10\text{Hz}$ $\text{NBW} = 1\text{Hz}$
CAPACITANCE						
C_{ISS}	Input	--	--	8	pF	$V_{DS} = 15\text{V}$ $I_D = 200\mu\text{A}$ $f = 1\text{MHz}$
C_{RSS}	Reverse Transfer	--	--	1.5	pF	

Note 1 – These ratings are limiting values above which the serviceability of any semiconductor may be impaired

Available Packages:

U404 / LSU404 in TO-71 & TO-78
U404 / LSU404 available as bare die
Please contact [Micross](http://www.micross.com) for full package and die dimensions

TO-71 / TO-78 (Top View)



Micross Components Europe



Tel: +44 1603 788967

Email: chipcomponents@micross.com

Web: <http://www.micross.com/distribution>