

3M™ Volition™

Punch Down RJ45 Panels – Category 5e and Category 6



Easy-to-use punch down panels which offer 24 ports in 1U, ideal for reliable, fast installation

The panels have a removable rear cable manager for cable strain relief and correct guiding of cables to the point of termination.

The panels are available in either category 5e UTP or category 6 UTP. Rounded edges on the front plate provide an aesthetic appearance and improved mechanical strength.

A full fixing kit is provided and wires can be punched down with either LSA or 110 tools. Panels have post numbering and space for individual port labelling.

The panels are available in black.

Features

- T568A or T568B wiring
- Terminates with LSA or 110 tools
- Removable cable retention bar

Benefits

- Universal application
- Widely available tool used for assembly
- Simplifies punch down, gives cable strain relief, controls cable bending and increased system performance

Specification

Electrical performance:	Category 5e panels meet TIA/EIA-568-B.1 Category 5e link standard and ISO/IEC 11801 and EN 50173-1 Class D performance Category 6 panels meet TIA/EIA-568-B.2.1 Category 6 link standard and ISO/IEC 11801 and EN 50173-1 Class E performance
Storage temperature:	-40° to +70°C
Operating temperature:	-10° to +60°C
Humidity:	max 93% (non condensing)
Colour:	black

Ordering Information

Ref. No.



24 port Category 5e Punch Down Patch Panel

VOL-PD-CAT5E-24P



24 port Category 6 Punch Down Patch Panel

VOL-PD-CAT6-24P

Important Notice

The details contained in this literature have been carefully prepared from information available to 3M at the time of its production. However, it is not intended to be relied upon for purposes of product specification and you should contact your sales representative if specification details are required. Because of the wide variety of processes and conditions in which these products may be used, the user should first carry out tests to determine the suitability of the products for the particular use intended. All questions of warranty and liability relating to 3M products are governed by the selling 3M subsidiary's Terms of Sale subject where applicable to the prevailing law.
3M is trademark of the 3M company. SID is a trademark of Quante AG.



3M Telecommunications

Europe, Middle East & Africa
c/o 3M Deutschland GmbH
Carl-Schurz-Straße 1

41453 Neuss · Germany

Tel.: ++49 (0)2131 / 14-5999

Fax: ++49 (0)2131 / 14-5998

Internet: www.3MTelecommunications.com/eu

Rights reserved to make technical alternations.

Edition XX/2009