


20V DUAL N AND P-CHANNEL ENHANCEMENT MODE MOSFET**SUMMARY****N-CHANNEL: $V_{(BR)DSS}=20V$; $R_{DS(ON)}=0.13\Omega$; $I_D=2.4A$** **P-CHANNEL: $V_{(BR)DSS}=-20V$; $R_{DS(ON)}=0.27\Omega$; $I_D=-1.7A$** **MSOP8****DESCRIPTION**

This new generation of high density MOSFETs from Zetex utilises a unique structure that combines the benefits of low on-resistance with fast switching speed. This makes them ideal for high efficiency, low voltage, power management applications.

FEATURES


- Low on-resistance
- Fast switching speed
- Low threshold
- Low gate drive
- Low profile SOIC package

**APPLICATIONS**

- DC - DC Converters
- Power Management Functions
- Disconnect switches
- Motor control

ORDERING INFORMATION

DEVICE	REEL SIZE (inches)	TAPE WIDTH (mm)	QUANTITY PER REEL
ZXMD63C02XTA	7	12mm embossed	1000 units
ZXMD63C02XTC	13	12mm embossed	4000 units

**DEVICE MARKING**

- ZXMD63C02

ZXMD63C02X

ABSOLUTE MAXIMUM RATINGS.


PARAMETER	SYMBOL	N-CHANNEL	P-CHANNEL	UNIT
Drain-Source Voltage	V _{DSS}	20	-20	V
Gate- Source Voltage	V _{GS}		± 12	V
Continuous Drain Current (V _{GS} =4.5V; T _A =25°C)(b)(d) (V _{GS} =4.5V; T _A =70°C)(b)(d)	I _D	2.4 1.9	-1.7 -1.35	A
Pulsed Drain Current (c)(d)	I _{DM}	19	-9.6	A
Continuous Source Current (Body Diode)(b)(d)	I _S	-1.5	-1.4	A
Pulsed Source Current (Body Diode)(c)(d)	I _{SM}	19	-9.6	A
Power Dissipation at T _A =25°C (a)(d) Linear Derating Factor	P _D	0.87 6.9		W mW/°C
Power Dissipation at T _A =25°C (a)(e) Linear Derating Factor	P _D	1.04 8.3		W mW/°C
Power Dissipation at T _A =25°C (b)(d) Linear Derating Factor	P _D	1.25 10		W mW/°C
Operating and Storage Temperature Range	T _j ;T _{stg}	-55 to +150		°C

THERMAL RESISTANCE

PARAMETER	SYMBOL	VALUE	UNIT
Junction to Ambient (a)(d)	R _{θJA}	143	°C/W
Junction to Ambient (b)(d)	R _{θJA}	100	°C/W
Junction to Ambient (a)(e)	R _{θJA}	120	°C/W


NOTES

- (a) For a device surface mounted on 25mm x 25mm FR4 PCB with high coverage of single sided 1oz copper, in still air conditions
- (b) For a device surface mounted on FR4 PCB measured at t≤10 secs.
- (c) Repetitive rating - pulse width limited by maximum junction temperature. Refer to Transient Thermal Impedance graph.
- (d) For device with one active die.
- (e) For device with two active die running at equal power.

N-CHANNEL CHARACTERISTICS

ZXMD63C02X

P-CHANNEL CHARACTERISTICS



**N-CHANNEL
ELECTRICAL CHARACTERISTICS (at $T_{amb} = 25^\circ\text{C}$ unless otherwise stated).**

PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT	CONDITIONS.
STATIC						
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	20			V	$I_D=250\mu\text{A}, V_{GS}=0\text{V}$
Zero Gate Voltage Drain Current	I_{DSS}			1	μA	$V_{DS}=20\text{V}, V_{GS}=0\text{V}$
Gate-Body Leakage	I_{GSS}			100	nA	$V_{GS}=\pm 12\text{V}, V_{DS}=0\text{V}$
Gate-Source Threshold Voltage	$V_{GS(\text{th})}$	0.7			V	$I_D=250\mu\text{A}, V_{DS}= V_{GS}$
Static Drain-Source On-State Resistance (1)	$R_{DS(\text{on})}$			0.130 0.150	Ω	$V_{GS}=4.5\text{V}, I_D=1.7\text{A}$ $V_{GS}=2.7\text{V}, I_D=0.85\text{A}$
Forward Transconductance (3)	g_{fs}	2.6			S	$V_{DS}=10\text{V}, I_D=0.85\text{A}$
DYNAMIC (3)						
Input Capacitance	C_{iss}		350		pF	
Output Capacitance	C_{oss}		120		pF	$V_{DS}=15\text{ V}, V_{GS}=0\text{V}, f=1\text{MHz}$
Reverse Transfer Capacitance	C_{rss}		50		pF	
SWITCHING(2) (3)						
Turn-On Delay Time	$t_{d(\text{on})}$		3.4		ns	
Rise Time	t_r		8.1		ns	$V_{DD}=10\text{V}, I_D=1.7\text{A}$
Turn-Off Delay Time	$t_{d(\text{off})}$		13.5		ns	$R_G=6.0\Omega, R_D=5.7\Omega$ (Refer to test circuit)
Fall Time	t_f		9.1		ns	
Total Gate Charge	Q_g			6	nC	
Gate-Source Charge	Q_{gs}			0.65	nC	$V_{DS}=16\text{V}, V_{GS}=4.5\text{V}, I_D=1.7\text{A}$
Gate Drain Charge	Q_{gd}			2.5	nC	(Refer to test circuit)
SOURCE-DRAIN DIODE						
Diode Forward Voltage (1)	V_{SD}			0.95	V	$T_j=25^\circ\text{C}, I_S=1.7\text{A}, V_{GS}=0\text{V}$
Reverse Recovery Time (3)	t_{rr}		15.0		ns	$T_j=25^\circ\text{C}, I_F=1.7\text{A}, dI/dt= 100\text{A}/\mu\text{s}$
Reverse Recovery Charge(3)	Q_{rr}		5.9		nC	


(1) Measured under pulsed conditions. Width=300μs. Duty cycle ≤2% .

(2) Switching characteristics are independent of operating junction temperature.


(3) For design aid only, not subject to production testing.

ZXMD63C02X

N-CHANNEL TYPICAL CHARACTERISTICS



N-CHANNEL CHARACTERISTICS



ZXMD63C02X

P-CHANNEL ELECTRICAL CHARACTERISTICS (at $T_{amb} = 25^\circ C$ unless otherwise stated).


PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT	CONDITIONS.
STATIC						
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	-20			V	$I_D=-250\mu A, V_{GS}=0V$
Zero Gate Voltage Drain Current	I_{DSS}			-1	μA	$V_{DS}=-20V, V_{GS}=0V$
Gate-Body Leakage	I_{GSS}			± 100	nA	$V_{GS}=\pm 12V, V_{DS}=0V$
Gate-Source Threshold Voltage	$V_{GS(th)}$	-0.7			V	$I_D=-250\mu A, V_{DS}=V_{GS}$
Static Drain-Source On-State Resistance (1)	$R_{DS(on)}$			0.27 0.40	Ω	$V_{GS}=-4.5V, I_D=-1.2A$ $V_{GS}=-2.7V, I_D=-0.6A$
Forward Transconductance (3)	g_{fs}	1.3			S	$V_{DS}=-10V, I_D=-0.6A$
DYNAMIC (3)						
Input Capacitance	C_{iss}		290		pF	
Output Capacitance	C_{oss}		120		pF	$V_{DS}=-15 V, V_{GS}=0V, f=1MHz$
Reverse Transfer Capacitance	C_{rss}		50		pF	
SWITCHING(2) (3)						
Turn-On Delay Time	$t_{d(on)}$		3.4		ns	
Rise Time	t_r		9.6		ns	$V_{DD}=-10V, I_D=-1.2A$
Turn-Off Delay Time	$t_{d(off)}$		16.4		ns	$R_G=6.0\Omega, R_D=8.3\Omega$ (Refer to test circuit)
Fall Time	t_f		20.4		ns	
Total Gate Charge	Q_g			5.25	nC	
Gate-Source Charge	Q_{gs}			1.0	nC	$V_{DS}=-16V, V_{GS}=-4.5V, I_D=-1.2A$
Gate Drain Charge	Q_{gd}			2.25	nC	(Refer to test circuit)
SOURCE-DRAIN DIODE						
Diode Forward Voltage (1)	V_{SD}			-0.95	V	$T_j=25^\circ C, I_S=-1.2A, V_{GS}=0V$
Reverse Recovery Time (3)	t_{rr}		21.7		ns	$T_j=25^\circ C, I_F=-1.2A, di/dt= 100A/\mu s$
Reverse Recovery Charge(3)	Q_{rr}		9.6		nC	

(1) Measured under pulsed conditions. Width=300 μs . Duty cycle $\leq 2\%$.

(2) Switching characteristics are independent of operating junction temperature.







(3) For design aid only, not subject to production testing.

P-CHANNEL CHARACTERISTICS




ZXMD63C02X

P-CHANNEL TYPICAL CHARACTERISTICS




ZXMD63C02X

PACKAGE DIMENSIONS



DIM	Millimetres		Inches	
	MIN	MAX	MIN	MAX
A			1.10	0.043
A1	0.05	0.15	0.002	0.006
B	0.25	0.40	0.010	0.016
C	0.13	0.23	0.005	0.009
D	2.90	3.10	0.114	0.122
e	0.65	BSC	0.0256	BSC
E	2.90	3.10	0.114	0.122
H	4.90	BSC	0.193	BSC
L	0.40	0.70	0.016	0.028
q°	0°	6°	0°	6°

PAD LAYOUT DETAILS



ZETEX

Zetex plc.

Fields New Road, Chadderton, Oldham, OL9-8NP, United Kingdom.
Telephone: (44)161 622 4422 (Sales). (44)161 622 4444 (General Enquiries)
Fax: (44)161 622 4420

Zetex GmbH
Streifeldstraße 19
D-81673 München
Germany
Telefon: (49) 89 45 49 49 0
Fax: (49) 89 45 49 49 49

Zetex Inc.
47 Mall Drive, Unit 4
Commack NY 11725
USA
Telephone: (516) 543-7100
Fax: (516) 864-7630

Zetex (Asia) Ltd.
3510 Metroplaza, Tower 2
Hing Fong Road,
Kwai Fong, Hong Kong
Telephone: (852) 26100 611
Fax: (852) 24250 494

These are supported by
agents and distributors in
major countries world-wide
©Zetex plc 1999
Internet: <http://www.zetex.com>

This publication is issued to provide outline information only which (unless agreed by the Company in writing) may not be used, applied or reproduced for any purpose or form part of any order or contract or be regarded as a representation relating to the products or services concerned. The Company reserves the right to alter without notice the specification, design, price or conditions of supply of any product or service.