

Part Number: C3113

Revision Level: 0

Date: 7/7/2007

**4C 18 7/26 BC FLEX FLEX**

**TYPE CMP / CL3P**

**A. CONSTRUCTION**

Conductor: #18 AWG 7/26 Bare Copper  
 Insulation: 0.008" Wall FLEXGUARD\*  
 Cable: 4 Conductors @ 4.00" LHL.  
 Jacket: 0.015" Wall FLEXGUARD\* - Natural  
 -Plenum ripcord under jacket.

**DIAMETERS**

0.047" nom.  
 0.063" nom.  
 0.152" nom.  
 0.182" +/- 0.009"

Print Legend: **CAROL (R) 18 AWG -- C3113 -- 75C E60233-8 (UL) CL3P --- C(UL) CMP -- MADE IN USA**  
**DATE CODE (PRINT EVERY 2 FT)**

**B. INDUSTRY APPROVALS**

National Electrical Code Article 725  
 UL Standard 13 Type CL3P

National Electrical Code Article 800  
 UL Standard 444 Type CMP

**C. ELECTRICAL PROPERTIES**

TEMPERATURE: 75C  
 SUGGESTED WORKING VOLTAGE (Vrms): 150 Vrms (CL3P) / 300Vrms (CMP)  
 CONDUCTOR D.C. RESISTANCE: 5.6 Ohms/1000 ft. nom. @ 20C

**D. COLOR CODE** (Listed as Individual Conductors or Pairs of Conductors)

1	Black
2	White
3	Red
4	Green

Note: Data are subject to change without notice. Contact your Customer Service representative for latest information.

\*FLEXGUARD is a trademark of General Cable Corporation for polymer alloy insulation and jackets.