

Part Number: C9013ZH

Revision Level: 0

Date: April 4, 2012

8C22 FR-LSZH, UNSHIELDED FR-LSZH Jacket

EXZEL™ FR-LSZH Cable

A. CONSTRUCTION

- | | | | |
|-----|---------------|---|-------------|
| 1.0 | CONDUCTOR: | #22AWG (7/30) Tinned Copper | 0.030" nom. |
| 2.0 | INSULATION: | 0.010" Wall FR-LSZH Polyolefin | 0.050" nom. |
| 3.0 | COLOR CODE: | Black, Brown, Red, Orange, Yellow, Green, Blue, Violet | |
| 4.0 | CABLE: | 8/Conductors Cabled LHL | |
| 5.0 | FILLERS: | Fibrillated Polypropylene as needed for roundness | |
| 6.0 | TAPE: | Polyester Tape Wrap, 25% Overlap | |
| 7.0 | JACKET: | 0.037" Wall Gray FR-LSZH Polyolefin | 0.243" Nom. |
| 8.0 | PRINT LEGEND: | <i>CAROL ® EXZEL™ – C9013ZH – 8/C 22 AWG E86009 (UL) CL2 OR PLTC-ER OR CM c(UL) 105C -- OIL RES-I SUN RES -- FT4/IEEE 1202 (-40C) -- FR-LSZH / RoHS / CE -- MADE IN USA (MFG& DATE CODE & SEQ FT)</i> | |

DIAMETERS

B. INDUSTRY APPROVALS

National Electrical Code UL Standard 13	Article 725 Type CL2 OR PLTC-ER
National Electrical Code UL Standard 444	Article 800 Type CM / CSA c(UL)us
CSA LS-ZH	CM c(UL)us; FT-4 IEC 60754-2

C. ELECTRICAL PROPERTIES

- | | | |
|----|-----------------------------------|---------------------------------|
| 1) | TEMPERATURE: | -40C to + 105C |
| 2) | SUGGESTED WORKING VOLTAGE (Vrms): | 300V Max. |
| 3) | CONDUCTOR D.C. RESISTANCE: | 15.72 Ohms/1000 ft. nom. @ 20 C |
| 4) | CABLE WEIGHT: | 41.20 LBS. /KFT nom. |



Note: Data are subject to change without notice. Contact your Customer Service representative for latest information.