


RING TERMINALS HEAVY DUTY

Vinyl Insulated Funnel Entry

- Insulation Support
- Brazed Seam



PANDUIT® Part Number	Wire Range	Color code	Max. Ins.	Stud Size	Dimensions (in.)				Std. Pkg. Qty.	Std. Ctn. Qty.	Bulk Pkg. Qty.	Bulk Ctn. Qty.	Crimp Tools
					A	W	C	G					
PV12-6HDR-L	16-12 .05 Stock	Yellow	.225	#6	1.05	.31	.35	.89	50	500	500	3000	CT-600‡ CT-1550‡ CT-1551‡
PV12-8HDR-L				#8	1.05	.31	.35	.89	50	500	500	3000	
PV12-10HDR-L				#10	1.08	.37	.33	.89	50	500	500	3000	
PV12-14HDR-L				1/4"	1.23	.52	.42	.97	50	500	500	3000	
PV12-56HDR-L				5/16"	1.23	.52	.42	.97	50	500	500	3000	
PV12-38HDR-L				3/8"	1.31	.58	.46	1.02	50	500	500	3000	

EXPANDED INSULATION


PV12-6HDRX-L	16-12 .05 Stock	Yellow	.250	#6	1.08	.31	.33	.95	50	500	500	3000	CT-600‡ CT-1550‡ CT-1551‡
PV12-8HDRX-L				#8	1.08	.31	.33	.95	50	500	500	3000	
PV12-10HDRX-L				#10	1.15	.37	.31	.95	50	500	500	3000	
PV12-14HDRX-L				1/4"	1.30	.52	.40	1.03	50	500	500	3000	
PV12-56HDRX-L				5/16"	1.30	.52	.40	1.03	50	500	500	3000	
PV12-38HDRX-L				3/8"	1.38	.58	.44	1.10	50	500	500	3000	

RING TERMINALS LARGE WIRE

Vinyl Insulated

- Insulation Support
- #8 through #2 AWG wire sizes. Heavy duty construction for demanding applications


- Brazed Seam



PV8-8R-Q	8 .040 Stock	Red	.280	#8	1.51	.42	.43	1.29	25	250	200	1200	CT-720 CD-720PV8-2^
PV8-10R-Q				#10	1.53	.47	.43	1.29	25	250	200	1200	
PV8-14R-Q				1/4"	1.53	.47	.43	1.29	25	250	200	1200	
PV8-56R-Q				5/16"	1.64	.59	.49	1.34	25	250	200	1200	
PV8-38R-Q				3/8"	1.64	.59	.51	1.34	25	250	200	1200	
PV8-12R-Q	1/2"	1.74	.82	.54	1.34	25	250	200	1200				
PV6-8R-E	6 .045 Stock	Blue	.340	#8	1.61	.47	.43	1.38	20	200	200	1200	CT-720 CD-720PV8-2^
PV6-10R-E				#10	1.62	.47	.43	1.38	20	200	200	1200	
PV6-14R-E				1/4"	1.65	.47	.48	1.38	20	200	200	1200	
PV6-56R-E				5/16"	1.74	.62	.53	1.44	20	200	200	1200	
PV6-38R-E				3/8"	1.74	.62	.51	1.44	20	200	200	1200	
PV6-12R-E	1/2"	1.84	.82	.51	1.44	20	200	200	1200				
PV4-10R-E	4 .050 Stock	Yellow	.450	#10	1.88	.55	.50	1.61	20	200	200	1200	CT-720 CD-720PV8-2^
PV4-14R-E				1/4"	1.88	.55	.50	1.61	20	200	200	1200	
PV4-56R-E				5/16"	1.95	.68	.50	1.61	20	200	200	1200	
PV4-38R-E				3/8"	1.95	.68	.50	1.61	20	200	200	1200	
PV4-12R-E				1/2"	2.04	.86	.50	1.61	20	200	200	1200	
PV2-10R-X	2 .060 Stock	Red	.560	#10	1.96	.68	.58	1.62	10	100	200	1200	CT-720 CD-720PV8-2^
PV2-14R-X				1/4"	1.96	.68	.58	1.62	10	100	200	1200	
PV2-56R-X				5/16"	1.96	.68	.58	1.62	10	100	200	1200	
PV2-38R-X				3/8"	1.96	.68	.58	1.62	10	100	200	1200	
PV2-12R-X				1/2"	2.05	.86	.58	1.62	10	100	200	1200	

Vinyl Expanded Insulation

- For Large Wire Insulation O.D.
- Insulation Support
- Brazed Seam



PV8-8RX-Q	8 .040 Stock	Red	.360	#8	1.50	.42	.43	1.29	25	250	200	1200	CT-720 CD-720PV8-2^
PV8-10RX-Q				#10	1.52	.47	.43	1.29	25	250	200	1200	
PV8-14RX-Q				1/4"	1.52	.47	.43	1.29	25	250	200	1200	
PV8-56RX-Q				5/16"	1.62	.59	.51	1.33	25	250	200	1200	
PV8-38RX-Q				3/8"	1.62	.59	.51	1.33	25	250	200	1200	
PV8-12RX-Q	1/2"	1.74	.82	.51	1.33	25	250	200	1200				
PV6-8RX-E	6 .045 Stock	Blue	.436	#8	1.61	.47	.43	1.37	20	200	200	1200	CT-720 CD-720PV8-2^
PV6-10RX-E				#10	1.61	.47	.43	1.37	20	200	200	1200	
PV6-14RX-E				1/4"	1.61	.47	.43	1.37	20	200	200	1200	
PV6-56RX-E				5/16"	1.73	.62	.51	1.42	20	200	200	1200	
PV6-38RX-E				3/8"	1.73	.62	.53	1.42	20	200	200	1200	
PV6-12RX-E	1/2"	1.83	.82	.53	1.42	20	200	200	1200				
PV4-10RX-E	4 .050 Stock	Yellow	.515	#10	1.87	.55	.53	1.60	20	200	200	1200	CT-720 CD-720PV8-2^
PV4-14RX-E				1/4"	1.87	.55	.53	1.60	20	200	200	1200	
PV4-56RX-E				5/16"	1.94	.68	.53	1.60	20	200	200	1200	
PV4-38RX-E				3/8"	1.94	.68	.53	1.60	20	200	200	1200	
PV4-12RX-E				1/2"	2.03	.86	.53	1.60	20	200	200	1200	
PV2-10RX-X	2 .060 Stock	Red	.610	#10	1.95	.68	.57	1.61	10	100	200	1200	CT-720 CD-720PV8-2^
PV2-14RX-X				1/4"	1.93	.68	.57	1.61	10	100	200	1200	
PV2-56RX-X				5/16"	1.93	.68	.57	1.61	10	100	200	1200	
PV2-38RX-X				3/8"	1.94	.69	.57	1.61	10	100	200	1200	
PV2-12RX-X				1/2"	2.20	.86	.57	1.61	10	100	200	1200	

Order the number of pieces required in multiples of standard package quantities.

X=10 pcs., E=20 pcs., Q=25 pcs., L=50 pcs., T=200 pcs. and D=500 pcs.

‡UL and CSA approved tooling/product combinations.

^UL approved tooling/product combinations.

Prime items appear in **BOLD**.

For complete product and specification information visit our website at: www.panduit.com/eg or call: 800-777-3300

Sold exclusively through authorized PANDUIT distributors.