

5062	8451	6477	4477
<b>5062-0-00-XX-00-00-33-0</b> Solder mount in 0,74 mounting hole	<b>8451-0-00-XX-00-00-33-0</b> Solder mount in 0,74 mounting hole	<b>6477-0-00-XX-00-00-38-0</b> Solder mount in 0,86 mounting hole	<b>4477-0-00-XX-00-00-33-0</b> Solder mount in 0,86 mounting hole

8922	4268	9086	8330
<b>8922-0-00-XX-00-00-38-0</b> Solder mount in 0,86 mounting hole	<b>4268-0-00-XX-00-00-33-0</b> Solder mount in 0,99 mounting hole	<b>9086-0-00-XX-00-00-33-0</b> Solder mount in 1,02 mounting hole	<b>8330-0-00-XX-00-00-38-0</b> Solder mount in 1,12 mounting hole

6095	9228	6092						
<b>6095-X-00-XX-00-00-38-0</b> Solder mount in 1,12 mounting hole	<b>9228-0-00-XX-00-00-38-0</b> Solder mount in 1,12 mounting hole	<b>6092-0-00-XX-00-00-33-0</b> Solder mount in 1,12 mounting hole						
<table border="1"> <thead> <tr> <th>Basic Part Number</th> <th>Pin Length L</th> </tr> </thead> <tbody> <tr> <td>6095-0</td> <td>14,73</td> </tr> <tr> <td>6095-1</td> <td>12,07</td> </tr> </tbody> </table>			Basic Part Number	Pin Length L	6095-0	14,73	6095-1	12,07
Basic Part Number	Pin Length L							
6095-0	14,73							
6095-1	12,07							

<p><b>SPECIFICATIONS</b></p> <p><b>PIN MATERIAL:</b> Brass Alloy 360, 1/2 Hard (Except where noted)</p> <p><b>PART MANUFACTURED IN INCHES, METRIC FOR REF ONLY</b></p> <p><b>TOLERANCES ON:</b> LENGTHS: ± 0,13 DIAMETERS: ± 0,05 ANGLES: ± 2°</p>	<p><b>ORDER CODE: XXXX - X - 00 - XX - 00 - 00 - 3X - 0</b></p> <p><b>BASIC PART #</b> →</p> <p style="text-align: right;"><b>SPECIFY PIN FINISH:</b></p> <p><b>01</b> 5,08µm TIN/LEAD OVER NICKEL  <b>80</b> 5,08µm TIN OVER NICKEL <span style="color: green;">◇</span>  <b>15</b> 0,25µm GOLD OVER NICKEL <span style="color: green;">◇</span>  <b>21</b> 0,51µm GOLD OVER NICKEL <span style="color: green;">◇</span>  <b>34</b> 1,27µm GOLD OVER NICKEL <span style="color: green;">◇</span></p>	
--	---	--