

1

2

3

4

A

B

C

D

A

B

C

D

CONTACT LENGTH FOR ALL		TIN LEAD	ITEM
DIM-P ±0.10	DIM-D ±0.25	PART NUMBER	
5.75 ±0.10	4.25 ±0.25	HM1W59LPR178H6P	14
5.75 ±0.10	11.8 ±0.25	HM1W59LKR178H6P	

CONTACT LENGTH FOR ALL		LEAD FREE	ITEM
DIM-P ±0.10	DIM-D ±0.25	PART NUMBER	
5.75 ±0.10	4.25 ±0.25	HM1W59LPR178H6PLF	14
5.75 ±0.10	11.8 ±0.25	HM1W59LKR178H6PLF	

NOTE-1: "EYE OF THE NEEDLE" PRESS-FIT PIN TYPE

NOTE-2: CAVITY FOR CODING KEY MOUNTING AND CABLE CONNECTOR LATCH.

NOTE-3: INSERTION TOOLING ON PCB, SEE DRAWING REF C-8626-1002

NOTE-4: IF SUFFIX "P" IS ADDED IN P/N, PACKAGING IS IN TRAYS BUT CONNECTOR MARKING IS WITHOUT "P"
EXAMPLE: HM1W59LPR178H6P, MARKED HM1W59LPR178H6

GENERAL CHARACTERISTICS AND ROHS INFORMATIONS:

SEE PRODUCT SPECIFICATION GS-12-445

European Views

www.fciconnect.com			surface ISO 1302 ✓	tolerance std ISO 406 ISO 1101	projection mm
			TOLERANCES UNLESS OTHERWISE SPECIFIED		
Dr	ETIEMBRE	1997/01/08	ANGULAR 0.XX' ±2°	0.X	±0.1
Eng	CHAMPION	1997/01/08		0.XX	±0.1
Chr	M LENOIR	1997/01/08		0.XXX	±0.1
Appr	M LENOIR	1997/01/08		0.XXX	±0.1
			Product family	METRAL	
			ECN		LS07-0012
			Spec ref		-
			Title		METRAL 5 ROW 390 WAYS
			Male		MALE
			Catalog no		-
			Customer		sheet 1 of 1
			Rev.		E

REV F - 2006-04-17

1

2

3

4