

Part No.	Type	Nominal diameter	Withdraw. force	Rated current	Contact resistance
41.6007	B 1.25	1.25 mm	≈ 1 N	20 A	≈ 1 mΩ
	Socket 1.25 mm (.049 in) dia. with M 2 threaded post. Gold plated.				
22.1044	LS 1.25-B	1.25 mm	≈ 1 N	20 A	≈ 1 mΩ
	Socket 1.25 mm (.049 in) dia. with solder lug. Gold plated.				
	Matching insulator KT 2-S # 22.2010 pictured below.				
21.1160 (7.5 cm)	LK 1.25-B	1.25 mm	-	6 A	1 mΩ
21.1170 (15 cm)					
21.1180 (30 cm)					
21.1190 (45 cm)					
	Highly flexible patch cord with 1.25 mm (.049 in) dia. Socket: machined brass, gold plated with spring-loaded MC [®] -Multilam™. PVC insulated wire 0.5 mm ² (20 AWG).				
	Components and ratings:				
	• Socket LS 1.25-B # 22.1044				
	• Insulator (polyamide) KT 2-S # 22.2010				
	• Wire HK 0.5 PVC # 22.0010				
	• Operating temperature (wire): -10°C to + 70°C (14°F to 158°F)				
	• Operating temperature (insulator): -40°C to + 80°C (-40°F to 176°F)				
	Colors: 1-9				

0 - green/yellow 1 - red 2 - blue 3 - white 4 - black 5 - yellow 6 - green 7 - brown 8 - gray 9 - violet