




**Case Style DFS**


## Miniature Glass Passivated Single-Phase Surface Mount Bridge Rectifier

Reverse Voltage 50 to 1000V

Forward Current 1.0A



**Mounting Pad Layout**



### Mechanical Data

**Case:** Molded plastic body over passivated junctions

**Terminals:** Plated leads solderable per MIL-STD-750, Method 2026

**Polarity:** Polarity symbols marked on body

**Mounting Position:** Any

**Weight:** 0.04oz., 1.0g

**Packaging codes/options:**

27/1.5K per 13" Reel (16mm Tape)

45/50 EA. per Tube-Bulk

### Features

- Plastic package has Underwriters Laboratory Flammability Classification 94V-0
- This series is UL listed under Recognized Component Index, file number E54214
- Glass passivated chip junctions
- High surge overload rating of 30 Amperes peak
- Ideal for printed circuit boards
- High temperature soldering guaranteed: 260°C/10 seconds at 5 lbs. (2.3kg) tension

### Maximum Ratings and Thermal Characteristics (T<sub>A</sub> = 25°C unless otherwise noted)

Parameter	Symbol	DF005SA	DF01SA	DF02SA	DF04SA	DF06SA	DF08SA	DF10SA	Unit
Maximum repetitive peak reverse voltage	V <sub>RRM</sub>	50	100	200	400	600	800	1000	V
Maximum RMS voltage	V <sub>RMS</sub>	35	70	140	280	420	560	700	V
Maximum DC blocking voltage	V <sub>DC</sub>	50	100	200	400	600	800	1000	V
Maximum average forward output rectified current at T <sub>A</sub> = 40°C <sup>(2)</sup>	I <sub>F(AV)</sub>	1.0							A
Peak forward surge current single half sine-wave superimposed on rated load (JEDEC Method) T <sub>J</sub> = 150°C	I <sub>FSM</sub>	30							A
Rating for fusing (t < 8.3ms)	I <sup>2</sup> t	4.5							A <sup>2</sup> sec
Typical thermal resistance per leg <sup>(2)</sup>	R <sub>θJA</sub> R <sub>θJL</sub>	40 15							°C/W
Operating junction and storage temperature range	T <sub>J</sub> , T <sub>STG</sub>	-55 to +150							°C

### Electrical Characteristics (T<sub>A</sub> = 25°C unless otherwise noted)

Maximum instantaneous forward voltage drop per leg at 1.0A	V <sub>F</sub>	1.1	V
Maximum DC reverse current at rated DC blocking voltage per leg	I <sub>R</sub>	5.0 500	μA
Typical junction capacitance per leg <sup>(1)</sup>	C <sub>J</sub>	25	pF


**Notes:** (1) Measured at 1.0 MHz and applied reverse voltage of 4.0 Volts

(2) Units mounted on P.C.B. with 0.51 x 0.51" (13 x 13mm) copper pads


## Miniature Glass Passivated Single-Phase Surface Mount Bridge Rectifier

### Ratings and Characteristic Curves (T<sub>A</sub> = 25°C unless otherwise noted)


**Fig. 1 - Derating Curve Output Rectified Current**




**Fig. 2 - Maximum Non-Repetitive Peak Forward Surge Current Per Leg**




**Fig. 3 - Typical Forward Characteristics Per Leg**



**Fig. 4 - Typical Reverse Leakage Characteristics Per Leg**



**Fig. 5 - Typical Junction Capacitance Per Leg**



**Fig. 6 - Typical Transient Thermal Impedance**

